

HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

Project

FORTH REPLACEMENT CROSSING

Document title

Contractor

VIBRATION MONITORING REPORT SEPTEMBER 2015

00	07/10/15	First draft		MRN	SWR	SWR
Rev	Rev. Date	Purpose of revision Made Review			Reviewed	Approved
Docume	ent status					•
		FOR RE	VIEW			
Made by	/ Michael Richar	dson	Checked By: Ste	ven Westwa	ter	
Initials: MRN Initials: SWR						
Docume	ent number					Rev
REP-0	0251					00
		cual property of FCBC Construction JV. ss explicitly authorized.	Copying, distribu	ition, usage, a	and information	on contents

Forth Crossing Bridge Constructors - A Joint Venture of Hochtief Solutions AG, American Bridge International, Dragados, S.A. and Galliford Try Infrastructure Limited (Trading as Morrison Construction)



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

Contents

- 1. Introduction
- 2. Monitoring Summary
- 3. Conclusion

Appendices:

Appendix A: Vibration Assessments from Relevant PCNVs Appendix B: PPV and VDV Graphs



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

INTRODUCTION

- **1.1.** Monitoring of construction vibration is being undertaken by FCBC during the construction of the new Forth Crossing and associated road network. This report covers the month of September 2015. The objective of this report is to detail the vibration monitoring that has been undertaken across the site during this period, which has been done so in accordance with the Code of Construction Practice (CoCP), and Noise and Vibration Management Plan (NVMP).
- 1.2. FCBC carefully risk assesses noise & vibration likely to result from all construction activities, through the production of Plans for Control of Noise & Vibration (PCNVs). During the preparation of PCNVs, vibration prediction assessments are made. These assessments illustrate that no construction plant, equipment or methodology to be used by FCBC are envisaged to induce any levels of vibration at sensitive receptors that would exceed the vibration threshold levels stated in the CoCP. These assessments/predictions have been validated by means of the vibration monitoring results displayed in this report.



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

2. MONITORING SUMMARY

- 2.1. Due to the location and sensitivity of vibration monitoring equipment, the exceedances presented in the graphs included in the appendices of this report do not represent levels generated by construction, but rather show local interference around the monitoring equipment. This can include, for example, Residential activity, or indeed any significant movements occurring close to the monitoring equipment.
- 2.2. According to the BS5228-2 (2009) there is minimal documented proof of actual damage to structures or their finishes resulting from construction, and damage resulting solely from well-controlled construction and demolition vibrations is rare. There are many other mechanisms which cause damage, especially in decorative finishes, and it is often incorrectly concluded that vibrations from construction and demolition sites are to blame. In many cases it is not possible to ascertain the exact source of vibration, though it is possible to rule out construction as a source on an activity basis.
- **2.3.** The works carried out in each of the various construction work areas as well as the related vibration assessments are summarised in Appendix A.
- 2.4. Considering the distances between the various construction work areas and sensitive receptors as well as working methods utilised, the risk of any damage to structures or nuisance to residents occurring as a result FCBC construction related vibration is highly unlikely.
- **2.5.** The number of threshold exceedances at the various vibration monitoring stations during the period in question are shown in Table 1 below.



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

September 2015				
	PPV Exceedar	VDV Exceedance		
Location	Continuous (5 mm.s ⁻¹)	Intermittent (10 mm.s ⁻ 1)	Day (0.4 m.s ⁻ ^{1.75})	Night (0.2 m.s ^{-1.75})
Linn Mill	1	1	0	1
Butlaw Fisheries	1	0	0	0
Clufflat Brae	8	1	0	0
Dundas Home Farm	1	0	0	0
Echline	0	0	0	0
Inchgarvie Lodge	2	1	0	0
Scotstoun	0	1	0	0
Springfield	5	4	0	0
Tigh-Na- Grian	3	1	0	0
Whinnyhill	15	2	0	0

Table 1: Exceedances of thresholds set out in the CoCP

- 2.6. Peak Particle Velocity (PPV) is used to measure vibration through a solid surface. When a vibration is measured, the point at which the measurement takes place can be considered to have a particle velocity. This particle vibration will take place in three dimensions (x, y and z).
- **2.7.** The Peak Particle Velocity is the highest velocity that is recorded during a particular event, and as such is appropriate for the measurement of activities such as blasting, piling and compacting. The thresholds for the Forth Replacement Crossing are 5 mm.s⁻¹ for continuous construction (e.g. piling), and 10 mm.s⁻¹ for intermittent construction (e.g. blasting).
- **2.8.** These thresholds are set to protect against building damage. For this monitoring period, all the exceedances have been investigated thoroughly and appear to have been generated as a result of standalone, instantaneous events arising from local interferences, the exact source of which remains unknown.



- **2.9.** Vibration Dose Value (VDV) is a metric used in vibration monitoring. It is calculated by taking the fourth root of the integral of the fourth power of acceleration after it has been frequency-weighted. The frequency-weighted acceleration is measured in m.s⁻² and the time period over which the VDV is measured is in seconds. This yields VDVs in m.s^{-1.75}.
- **2.10.** The vibration dose value (VDV), a cumulative measurement of the vibration level received over an 8-hour or 16-hour period, is recommended in BS 6472 as the appropriate measure to evaluate human exposure to vibration in buildings in residential and other uses.
- **2.11.** During the monitoring period, vibratory rollers and whacker plates were used intermittently at several locations around the site. No exceedances were recorded as a result of the use of this equipment, where exceedances did occur it resulted from non-project related activity around the monitor.
- **2.12.** In addition, detailed investigation of all exceedances (i.e. review of PPV levels over 30 seconds periods) has shown that each resulted from isolated, non-construction related events, which likely occurred close to the monitoring station.
- **2.13.** Within the Appendix B, there are short gaps of missing data in the PPV and VDV graphs. These occurred due to a number of power supply problems and corrupt files.



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

3. CONCLUSION

- **3.1.** Considering the distance between FCBC construction works and sensitive receptors, the methods of working utilised and programme of works. The risk of damage to structures or nuisance to residents resulting from vibration is highly unlikely.
- **3.2.** Due to the location and sensitivity of vibration monitoring equipment, the exceedances presented in the graphs included in the appendices of this report are unlikely to be generated by construction, but rather show local interference and maintenance around the monitoring equipment.



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

APPENDIX A – MONITORING LOCATIONS & VIBRATION ASSESSMENTS FROM RELEVANT PCNVs



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

Table 2: Monitoring Locations

Ref.	Monitoring Location	Crossing or Network	Monitoring Locations Main Construction Activities During September 2015
			Earthworks/Fill placement
			New Ferrytoll Road
M1	Whinny Hill	Network	FT03&FT04 deck works
			• FT09 works
			• FT19 Works
			Roadworks
			Central Tower rebar, formwork, concreting works stay cable installation
M3	Tigh-Na-Grian	Crossing	 North Tower rebar, formwork, concreting works, deck section lifts, stay cable installation
			 Pier N1 rebar formwork & concrete works
			AVN works
			Pier S1 rebar, formwork & concrete works
			Pier S2 rebar, formwork and concete works
Μ7	Butlaw Fisheries	Crossing	Central Tower rebar, formwork, concreting works stay cable installation
			 South Tower rebar, formwork, concreting works, deck section lifts, stay cable installation
			Pile removal at pier S6
			 Scaffolding shuttering and reinforcement to deck.Pier S1 rebar, formwork & concrete works
			Rebar installation at Pier S2
	Inchgarvie Lodge	Crossing	 Central Tower rebar, formwork, concreting works Stay cable installation
M10			 South Tower rebar, formwork, concreting works stay cable installation, deck section lifts
			Main Carriageway earthworks
			Test pier removal
			Pile removal at pier S6
M11	Linn Mill	Network (close proximity to	 AVS – scaffolding, shuttering and reinforcement to deck.No night time or Sunday construction in the



		Crossing)	vicinity
			Pile removal at pier S6
			 Excavation, Break rock, fill/trim mainline & fill launch
		Crossing /	 AVS – scaffolding, shuttering and reinforcement to deck No night time or Sunday daytime construction in vicinity.
M13	Clufflat Brae	Network	Test pier removal
			Main carriageway roadworks
			• AVS – scaffolding, shuttering and reinforcement to deck Earthworks South Abutment area
M14	Springfield	Network	• Excavation, Break rock, fill/trim mainline & fill launch
			Test pier removal
			 AVS – scaffolding, shuttering and reinforcement to deck No night time or Sunday construction in the vicinity
M15	Echline	Network	Earthworks South Abutment area
			 Excavation, Break rock, fill/trim mainline & fill launch
			Footpath works
M16	Scotstoun	Network	Utility works
			B800 North road works including bridge works
			Footpath works
			Utility works
			Mainline Roadworks
M17	Dundas Home Farm	Network	•
			•
			B800 South roadworks including bridge works
			 Main carriageway works



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

Table 2: The main construction activities undertaken in the locality of each of the vibration monitors during the period of September 2015.

	Minimum distance	from work areas (m)	Type of vibration emitting	Worst case predic	ted vibration level
Monitor	Day (07:00-19:00)	Night (19:00-07:00)	plant/activity operated at nearest work areas	PPV (mm/s)	eVDV (m.s ^{-1.75})
Butlaw Fisheries	130	160	Roller/Whacker	0.44	0.23
Clufflat Brae	40	90	Roller/Whacker	2.44	0.37
Dundas	75	2000	Roller/Whacker	0.98	0.33
Echline	40	1000	Roller/Whacker	2.44	0.37
Inchgarvie Lodge	50	40	Roller/Whacker	1.77	0.33
Linn Mill	60	250	Roller/Whacker	1.36	0.33
Scotstoun	40	2000	Roller/Whacker	2.44	0.37
Springfield	50	300	Roller/Whacker	1.77	0.33
Tigh-Na-Grian	200	200	N/A	-	-
Whinny Hill	180	1800	N/A	-	-

Table 3: PCNV Predicted PPV & VDV Levels

Table 3: The distances from vibration monitors to the closest work areas for both day and night time periods. It also lists worst case PPV and eVDV calculations exhibited at the vibration monitors, resulting from the maximum vibration inducing plant operated at the nearest work areas.

Notes on Table 3


- All plant used during construction activities has been assessed with respect to vibration. The only plant utilised over the period in question considered to generate appreciable levels of vibration was a vibratory roller and a whacker plate (NOTE: Hydraulic rock breakers which typically generate 4.5mm/s @ 5m, 0.4mm/s @ 20m, 0.1mm/s @ 50m have been discounted due to the distances of use from the closest receptors).
- Vibratory rollers were not operated within 20m of any sensitive receptor. -
- Whacker plates were not utilised within 40m of any occupied sensitive receptor. -
- All roller eVDV values in the table above are based on the worst case scenario of a vibratory roller remaining in continuous operation for 2 hours an average distance (100m) from the nearest occupied receptors.
- All whacker plate eVDV values in the table above are based on the worst case scenario of a whacker plate remaining in continuous operation for 2 hours a minimum distance from the nearest receptor. -



APPENDIX B – VIBRATION GRAPHS



Forth Crossing Bridge Constructors




Forth Crossing Bridge Constructors - A Joint Venture of Hochtief Solutions AG, American Bridge International, Dragados, S.A. and Galliford Try Infrastructure Limited (Trading as Morrison Construction)


Exceedance on the 07/09/2015 has been investigated and found to be caused by maintenance of the noise monitor that is in close proximity of the vibration monitor. It is highly unlikely that the exceedance was caused by construction related activities (Graph above from the 07/09/2015).




Forth Crossing Bridge Constructors

















Exceedances from the 02/09/2015 to the 26/09/2015 have been investigated and found to be one off isolated events that are highly unlikely to be caused by construction related activities due to the distance away from the closest works which is approximately 200 meters away (graph above from the 02/09/2015).




Exceedance on the 30/09/2015 has been investigated and found to be caused by maintenance of the noise monitor that is in close proximity of the vibration monitor. It is highly unlikely that the exceedance was caused by construction related activities (Graph above from the 30/09/2015).






















on PPV
hreshold ttent on
hreshold ous on
PPV PPV
on
on data rertical axis ed as this is vertical, vibration

































Exceedance on the 28/09/2015, 29/09/2015 and on the 30/09/2015 have been investigated and found to be intermittent vibration which is unlikely to be caused by construction related activities and more likely to be caused by the localised construction of an extension of the nearby house (graph above from the 29/09/2015).




Due to similarity's in vibration levels at Linn mill and Inchgarvie lodge further investigation into the exceedances was carried out and it was found that the similarity's was a coincidence and were not related (reference graph above from the 28th of September).















Exceedances on the 28/09/2015 and on the 29/09/2015 have been investigated and found to be isolated events that are unlikely to be caused by construction related activities. It was also noted that the intermittent vibration levels happened within and out with construction working hours (graph above from the 28/09/2015).





Forth Crossing Bridge Constructors

on PPV
hreshold ttent on
hreshold ious on
PPV PPV
ion r
on data vertical axis ed as this is vertical, vibration
















Exceedance on the 01/09/2015 has been investigated and found to be a one off isolated event that is highly unlikely to be related to construction activities (graph above from the 01/09/2015).




6	
hreshold ttent on	
hreshold Ious Ion	
PPV : PPV ion r	
ion data	
vertical axis ed as this is e vertical, vibration	












Forth Crossing Bridge Constructors - A Joint Venture of Hochtief Solutions AG, American Bridge International, Dragados, S.A. and Galliford Try Infrastructure Limited (Trading as Morrison Construction)




Forth Crossing Bridge Constructors




All exceedances in the month of September at Springfield have been investigated and found unlikely to be caused by construction related activities. Exceedances on the 20/09/2015 and on the 22/09/2015 have been found to be out with construction working hours. Exceedances on the 01/09/2015, 02/09/2015, 04/09/2015, 07/09/2015, 12/09/2015, 26/09/2015 and on the 29/09/2015 have been investigated and found to be isolated events that are unlikely to be related to construction due to being approximately 265 meters away from the closest construction works (graph above from the 22/09/2015).















Measured highest Daily Peak Particle Velocity (PPV), Tigh-Na Grian,

All exceedances have been investigated and found to be one off isolated events that is unlikely to be caused by construction related activities (graph above from the 21/09/2015).




Forth Crossing Bridge Constructors


on PPV
hreshold ttent vn
hreshold ous on
PPV PPV
on r
on data ertical axis ed as this is vertical, <i>v</i> ibration
















Exceedance on the 02/09/2015, 03/09/2015, 04/09/2015, 05/09/2015, 06/09/2015, 13/09/2015, 24/09/2015, 26/09/2015 and on the 28/09/2015 have been investigated and found to be out of construction working hours and are unlikely to be caused by construction related activities (graph above from the 02/09/2015).



