



STRAINING POSTS -
(200 Ø min x 2300mm Long)
To be provided at all ends, acute corners and at intervals not greater than 150m on straight sections.

TURNING/CONTOUR POSTS -
(200 Ø min x 2500mm Long)
To be provided at obtuse corners and at acute ground undulations.

INTERMEDIATE POSTS -
(75 x 150 min X 2100mm Long)
To be provided at 1.8m centres max and at acute variations in level.

TIMBER POST AND RAIL WITH WIRE MESH TYPE F10

NOTES

1. All dimensions are in millimetres.
2. All posts and struts to be sawn timber.
3. BS 1722 Part 2 applies unless otherwise stated.
4. Galvanised high tensile stock fence HT8-80-15 Wire mesh to comply with BS 1722-2:2006
5. Details of posts and connections shall be in accordance with Drawing Nos. M8MF/JV/AW/003 F3 and 004 F4.
6. The wire shall be fixed on the field side of the fence unless otherwise stated.
7. Posts can be supported by rammed backfill or concrete ST2 as required.
8. 4 rail fence - BS 1722 part 7 applies unless otherwise stated.

CLIENT

PROJECT TITLE

M8 M73 M74
Motorway Improvements

REV	REVISIONS	BY	CHKD	APPD	DATE

This map is based upon Ordnance Survey material with the permission of Ordnance Survey, on behalf of the Controller of the Majesty's Stationery Office (C) Crown copyright and database right. Any use of the copyright material is authorised by express or implied licence from Ordnance Survey. No other use or copying is permitted without the express written permission of Ordnance Survey. Licence number: 100046668 2011.

DESIGN BY:	DM	CHECKED BY:	GG
DATE:	April 10	DATE:	April 10
DRAWN BY:	CF	APPROVED BY:	MB
DATE:	April 10	DATE:	April 10

ENGINEER

DRAWING TITLE

Accommodation Works
Timber Post & Rail With Wire Mesh
Type F10

SCALE @ A3 DRAWING NO. **M8MF/JV/AW/F-10**