



- NOTES**
1. VEHICLE HARD-STANDING TO BE CONSTRUCTED IN ACCORDANCE WITH DRAWING NDX1072-00 SHEET 2.
  2. ACCESS CONSIST OF CONTINUOUS WALKWAY WITH SITE PAVING. DISTANCE BETWEEN VEHICLE HARD-STANDING AND VMS SITE TO BE A MINIMUM CONSISTENT WITH NOTE 1 AND SITE TOPOLOGY.
  3. DUCTING AND CHAMBERS TO BE INSTALLED AS DRAWINGS NDX1063-01/02/03.
  4. THIS DRAWING IS A GENERAL ARRANGEMENT PROVIDING OUTLINE GUIDANCE ONLY.
  5. IT IS THE RESPONSIBILITY OF THE DESIGNER TO INCORPORATE THE OUTLINE GUIDANCE PROVIDED INTO A DESIGN CONFORMING TO ALL APPLICABLE REGULATIONS, REQUIREMENTS AND STANDARDS.



**SCOTTISH EXECUTIVE**

Traffic Controller Unit,  
EDINBURGH, EH8 8QQ

**NADICCS**  
www.nadics.org.uk

This drawing was generated on computer and must not be manually updated  
**TITLE** TYPICAL OVERALL VERGE MOUNTED MS3 400/320mm VMS  
**SITE** INFRASTRUCTURE

ORIGINAL DRAWING SIZE: 297 x 420
ALL DIMENSIONS ARE IN MM
TOLERANCE ± 1 UNLESS OTHERWISE STATED
THIRD ANGLE PROJECTION DO NOT SCALE

ISSUE	AMENDMENTS	APPD/DATE	
2	RE-ISSUED INCLUDING COMMENTS	BD 05/02/06	
1	FIRST ISSUE	BD 13/01/06	
DRN	C.S.G.	CHKD B.D.	
DATE	13.12.05	DATE	13.01.06
DRG. NO.	NDX1047-02ga		
SHT. NO.	1 of 2		