

HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

Project

FORTH REPLACEMENT CROSSING

Document title

Contractor

VIBRATION MONITORING REPORT DECEMBER 2013

00	17/01/2013	First Revision	ELS	MWN	MWN
Rev	Rev. Date	Purpose of revision	Made	Reviewed	Approved
		FOR APPROVAL			
Made by	y Euan Lucas	Checked By: Ma	artin Wilson		
Initials:	ELS	Initials: M	WN		
	ELS ent number	Initials: M	WN		Rev
	ent number	Initials: M	WN		Rev 00

Forth Crossing Bridge Constructors - A Joint Venture of Hochtief Solutions AG, American Bridge International, Dragados, S.A. and Galliford Try Infrastructure Limited (Trading as Morrison Construction)



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

Contents

- 1. Introduction
- 2. Monitoring Summary
- 3. Conclusion

Appendices:

•

Appendix A: Vibration Assessments from Relevant PCNVs Appendix B: PPV and VDV Graphs



American Bridge International DRAGADOS Morrison Construction

INTRODUCTION

- **1.1.** Monitoring of construction vibration is being undertaken by FCBC during the construction of the new Forth Crossing and associated road network. This report covers the month of December 2013. The objective of this report is to detail the vibration monitoring that has been undertaken across the site during this period, which has been done so in accordance with the Code of Construction Practice (CoCP), and Noise and Vibration Management Plan (NVMP).
- 1.2. FCBC have risk assessed noise & vibration resulting from all construction activities through the production of Plans for Control of Noise & Vibration (PCNVs). During the preparation of the PCNVs, the assessment/prediction of vibration levels has illustrated that no construction plant, equipment or methodology to be utilised by FCBC during the period in question, was envisaged to induce any levels of vibration at receptors that would exceed the vibration threshold levels stated in the CoCP. These assessments/predictions have been validated by means of the vibration monitoring results displayed in this report.



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

2. MONITORING SUMMARY

- 2.1. Due to the location and sensitivity of vibration monitoring equipment, the exceedances presented in the graphs included in the appendices of this report do not represent levels generated by construction, but rather show local interference around the monitoring equipment. This can include, for example, doors being slammed, or indeed any significant movements occurring close to the monitoring equipment.
- 2.2. According to the BS5228-2 (2009) there is minimal documented proof of actual damage to structures or their finishes resulting from construction, and damage resulting solely from well-controlled construction and demolition vibrations is rare. There are many other mechanisms which cause damage, especially in decorative finishes, and it is often incorrectly concluded that vibrations from construction and demolition sites are to blame. In many cases it is not possible to ascertain the exact source of vibration, though it is possible to rule out construction as a source on an activity basis.
- **2.3.** The works carried out in each of the various construction work areas as well as the related vibration assessments are summarised in Appendix A.
- 2.4. Considering the distances between the various construction work areas and sensitive receptors as well as working methods utilised, the risk of any damage to structures or nuisance to residents occurring as a result FCBC construction related vibration is highly unlikely.
- **2.5.** The number of threshold exceedances at the various vibration monitoring stations during the period in question are shown in Table 1 below.



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

December 2013					
	PPV Exc	eedance	VDV Exceedance		
Location	Continuous (5 mm.s ⁻¹)	Intermittent (10 mm.s ⁻¹)	Day (0.4 m.s ^{-1.75})	Night (0.2 m.s ^{-1.75})	
Linn Mill	0	0	0	3	
Butlaw Fisheries	0	0	0	0	
Clufflat Brae	1	0	0	0	
Dundas Home Farm	0	0	0	0	
Echline	1	1	0	0	
Inchgarvie Lodge	0	0	0	0	
Scotstoun	0	0	0	0	
Springfield	2	4	0	1	
Tigh-Na-Grian	4	1	0	0	
Whinnyhill	3	0	0	0	

Table 1: Exceedances of thresholds set out in the CoCP

- 2.6. Peak Particle Velocity (PPV) is used to measure vibration through a solid surface. When a vibration is measured, the point at which the measurement takes place can be considered to have a particle velocity. This particle vibration will take place in three dimensions (x, y and z).
- **2.7.** The Peak Particle Velocity is the highest velocity that is recorded during a particular event, and as such is appropriate for the measurement of activities such as blasting and piling. The thresholds for the Forth Replacement Crossing are 5 mm.s⁻¹ for continuous construction (e.g. piling), and 10 mm.s⁻¹ for intermittent construction (e.g. blasting).
- **2.8.** These thresholds are set to protect against building damage. For this monitoring period, all the exceedances have been investigated thoroughly and appear to have been generated as a result of standalone, instantaneous events arising from local interferences, the exact source of which remains unknown.
- **2.9.** Vibration Dose Value (VDV) is a metric used in vibration monitoring. It is calculated by taking the fourth root of the integral of the fourth power of acceleration after it has been frequency-weighted. The frequency-weighted acceleration is measured in m.s⁻² and the time period over which the VDV is measured is in seconds. This yields VDVs in m.s^{-1.75}.



- 2.10. The vibration dose value (VDV), a cumulative measurement of the vibration level received over an 8-hour or 16-hour period, is recommended in BS 6472 as the appropriate measure to evaluate human exposure to vibration in buildings in residential and other uses.
- 2.11. During the monitoring period, vibratory rollers and whacker plates were used intermittently at several locations around the site. Due to the distances between the work areas and any sensitive receptors, none of the exceedances in VDV levels can be associated with the use of vibratory rollers or whacker plates.
- **2.12.** In addition, detailed investigation of all exceedances (i.e. review of PPV levels over 30 seconds periods) has shown that each resulted from isolated, non-construction related events, which likely occurred close to the monitoring station.
- **2.13.** Within the Appendix B, there are short gaps of missing data in the PPV and VDV graphs. These occurred as a result of monitoring device errors.



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

3. CONCLUSION

- **3.1.** Considering the distance between FCBC construction works and sensitive receptors, and the methods of working utilised, the risk of damage to structures or nuisance to residents resulting from vibration is highly unlikely.
- **3.2.** Due to the location and sensitivity of vibration monitoring equipment, the exceedances presented in the graphs included in the appendices of this report do not represent levels generated by construction, but rather show local interference around the monitoring equipment.



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

APPENDIX A – MONITORING LOCATIONS & VIBRATION ASSESSMENTS FROM RELEVANT PCNVs



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

	M = 11	One a - !	- Main Construction: Asticities Deale	
Ref.	Monitoring Location	Crossing or Network	Main Construction Activities During December 2013	
M1	Whinny Hill	Network	 Drainage, kerbing and placing of Type 1 at Castlandhill Road N.B. No evening, night time or Sunday daytime construction in vicinity. 	
МЗ	Tigh-Na- Grian	Crossing	 Central Tower rebar, formwork & concreting works North Tower rebar, formwork & concreting works North Tower crane platform construction Pier N1 de-stressing wells & trestle bridge foundation works 	
M7	Butlaw Fisheries	Crossing	 Central Tower rebar, formwork & concreting works South Tower rebar, formwork & concreting works Pier S1 de-stressing wells works Pier S3 cofferdam construction Pier S5 rebar, formwork & concreting works Preparation of rebar prefabrication area at S5 causeway Fixing rebar at S6 Society Road Planting Concreting, fixing rebar and installation of tie beam at S7/S8 	
M10	Inchgarvie Lodge	Crossing	 Central Tower rebar, formwork & concreting works South Tower rebar, formwork & concreting works Pier S1 de-stressing wells works Pier S3 cofferdam construction Pier S5 rebar, formwork & concreting works Preparation of rebar prefabrication area at S5 causeway Fixing rebar at S6 Society Road Planting Concreting, fixing rebar and installation of tie beam at S7/S8 Launch – delivery and assembly of steel sections South abutment – launch of west section 	
M11	Linn Mill	Network	 Society Road Planting Concreting, fixing rebar and installation of tie beam at S7/S8 	

Table 2: Monitoring Locations

Forth Crossing Bridge Constructors - A Joint Venture of Hochtief Solutions AG, American Bridge International, Dragados, S.A. and Galliford Try Infrastructure Limited (Trading as Morrison Construction)



HOCHTIEF Solutions American Bridge International DRAGADOS Morrison Construction

			 Launch – delivery and assembly of steel sections South abutment – launch of west section N.B. No evening, night time or Sunday daytime construction in vicinity.
M13	Clufflat Brae	Network	 Society Road Planting Concreting, fixing rebar and installation of tie beam at S7/S8 Launch – delivery and assembly of steel sections South abutment – launch of west section N.B. No evening, night time or Sunday daytime construction in vicinity.
M14	Springfield	Network	 Launch – delivery and assembly of steel sections South abutment – launch of west section N.B. No evening, night time or Sunday daytime construction in vicinity.
M15	Echline Field	Network	 Launch – delivery and assembly of steel sections South abutment – launch of west section Echline cut – ripping rock and crushing Gyratory – rebar works and concreting A904 tie in road works, including drainage works and placing of Type 1 to west N.B. No evening, night time or Sunday daytime construction in vicinity.
M16	Scotstoun	Network	 Utilities works Structure works N.B. No evening, night time or Sunday daytime construction in vicinity.
M17	Dundas Home Farm	Network	 Utility works N.B. No evening, night time or Sunday daytime construction in vicinity.

Table 2 lists the main construction activities undertaken in the locality of each of the vibration monitors during the period of December 2013.

	Minimum distance from work areas (m)		Type of vibration emitting	Worst case predicted vibration level	
Monitor	Day (07:00-19:00)	Night (19:00-07:00)	plant/activity operated at nearest work areas	PPV (mm/s)	eVDV (m.s ^{-1.75})
Butlaw Fisheries	130	160	Roller/Whacker	0.44	0.23
Clufflat Brae	40	90	Roller/Whacker	2.44	0.37
Dundas	75	2000	Roller/Whacker	0.98	0.33
Echline	40	1000	Roller/Whacker	2.44	0.37
Inchgarvie Lodge	50	40	Roller/Whacker	1.77	0.33
Linn Mill	60	250	Roller/Whacker	1.36	0.33
Scotstoun	40	2000	Roller/Whacker	2.44	0.37
Springfield	50	300	Roller/Whacker	1.77	0.33
Tigh-Na-Grian	200	200	N/A	-	-
Whinny Hill	180	1800	N/A	-	-

Table 3: PCNV Predicted PPV & VDV Levels

Table 3 lists the distances from vibration monitors to the closest work areas for both day and night time periods. It also lists worst case PPV and eVDV calculations exhibited at the vibration monitors, resulting from the maximum vibration inducing plant operated at the nearest work areas.

Notes on Table 3

- All plant used during construction activities has been assessed with respect to vibration. The only plant utilised over the period in question considered to generate appreciable levels of vibration was a vibratory roller and a whacker plate (NOTE: Hydraulic rock breakers which typically generate 4.5mm/s @ 5m, 0.4mm/s @ 20m, 0.1mm/s @ 50m have been discounted due to the distances of use from the closest receptors).
- Vibratory rollers were not operated within 20m of any sensitive receptor. -
- Whacker plates were not utilised within 40m of any occupied sensitive receptor. -
- All roller eVDV values in the table above are based on the worst case scenario of a vibratory roller remaining in continuous operation for 2 hours an average distance (100m) from the nearest occupied receptors.
- All whacker plate eVDV values in the table above are based on the worst case scenario of a whacker plate remaining in continuous operation for 2 hours a minimum distance from the nearest receptor. -



APPENDIX B – VIBRATION GRAPHS



Forth Crossing Bridge Constructors



Measured highest Daily Peak Particle Velocity (PPV), 5 Linn Mill,

Notes:

- The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Linn Mill monitor on Sundays or during the Christmas period (24th December to 5th • of January).
- Data is missing for the period $\frac{25}{12} \frac{31}{12} \frac{31}{12}$ due to device error.



Forth Crossing Bridge Constructors



- The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Linn Mill monitor on Sundays or during the Christmas period (24th December to 5th) of January).
- Data is missing for the period $\frac{25}{12} \frac{31}{12} \frac{31}{12}$ due to device error.



Forth Crossing Bridge Constructors



- The grey areas of the chart represent the days on which no construction works were undertaken; no night time works were conducted in the vicinity of the Linn Mill vibration monitor throughout the month of December 2013. This • graph is included for illustrative purposes only.
- Data is missing for the period 25/12/13 31/12/13 due to device error.



Forth Crossing Bridge Constructors

on VDV
time VDV or dwellings
VDV
ne VDV
n
on data ertical axis ed as this is vertical, vibration



Measured highest Daily Peak Particle Velocity (PPV), Butlaw Fisheries,

Notes:

• The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted on 25th and 26th December 2013.



Forth Crossing Bridge Constructors



• The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted on 25th and 26th December 2013.



Forth Crossing Bridge Constructors



• The grey areas of the chart represent the days on which no construction works were undertaken; no night time works were conducted over the Christmas period (20th December to 5th January).



Forth Crossing Bridge Constructors



• The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Clufflat Brae monitor on Sundays or during the Christmas period (24th December to 5th of January).



Forth Crossing Bridge Constructors

on PPV
hreshold ttent on
hreshold ous m
/DV PPV
ion -
on data ertical axis ed as this is vertical, vibration



• The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Clufflat Brae monitor on Sundays or during the Christmas period (24th December to 5th of January).



Forth Crossing Bridge Constructors



• The grey areas of the chart represent the days on which no construction works were undertaken; no night time works were conducted in the vicinity of the Clufflat Brae vibration monitor throughout the month of December 2013. This graph is included for illustrative purposes only.



Forth Crossing Bridge Constructors

on VDV
time VDV or dwellings
VDV
ne VDV
on
ion data vertical axis ed as this is vertical, vibration



Measured highest Daily Peak Particle Velocity (PPV), Dundas Home Farm,

Notes:

• The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Dundas monitor on Sundays or during the Christmas period (21st December to 5th of January).



Forth Crossing Bridge Constructors

n	PPV	



• The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Dundas monitor on Sundays or during the Christmas period (21st December to 5th of January).



Forth Crossing Bridge Constructors



• The grey areas of the chart represent the days on which no construction works were undertaken; no night time works were conducted in the vicinity of the Dundas Home Farm vibration monitor throughout the month of December 2013. This graph is included for illustrative purposes only.



Forth Crossing Bridge Constructors

on VDV
time VDV or dwellings
VDV
ne VDV
on
ion data vertical axis ed as this is e vertical, vibration



• The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Echline monitor on Sundays or during the Christmas period (21st December to 5th of January).



Forth Crossing Bridge Constructors

on PPV S
hreshold ttent on
hreshold lous on
/DV : PPV ion
r
on data vertical axis ed as this is vertical, vibration



• The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Echline monitor on Sundays or during the Christmas period (21st December to 5th of January).



Forth Crossing Bridge Constructors



• The grey areas of the chart represent the days on which no construction works were undertaken; no night time works were conducted in the vicinity of the Echline vibration monitor throughout the month of December 2013. This graph is included for illustrative purposes only.



Forth Crossing Bridge Constructors

on VDV
time VDV For dwellings
VDV
me VDV
on
ion data vertical axis ed as this is e vertical, vibration



Measured highest Daily Peak Particle Velocity (PPV), Inchgarvie Lodge,

Notes:

- The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted on 25th and 26th December 2013.
- Data is missing for the period $\frac{24}{12} \frac{31}{12}{13}$ due to device error.



Forth Crossing Bridge Constructors



- The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted on 25th and 26th December 2013.
- Data is missing for the period $\frac{24}{12} \frac{31}{12}$ due to device error.



Forth Crossing Bridge Constructors



- The grey areas of the chart represent the days on which no construction works were undertaken; no night time works were conducted over the Christmas period (20th December to 5th January).
- Data is missing for the period $\frac{24}{12} \frac{31}{12}$ due to device error.



Forth Crossing Bridge Constructors

time VDV or dwellings	
VDV	
ne VDV	
n	



Measured highest Daily Peak Particle Velocity (PPV), Scotstoun,

Notes:

• The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Scotstoun monitor on Sundays or during the Christmas period (21st December to 5th) of January).



Forth Crossing Bridge Constructors

hreshold	
ttent	
n	
hreshold	
ous	



• The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Scotstoun monitor on Sundays or during the Christmas period (21st December to 5th) of January).



Forth Crossing Bridge Constructors



• The grey areas of the chart represent the days on which no construction works were undertaken; no night time works were conducted in the vicinity of the Scotstoun vibration monitor throughout the month of December 2013. This graph is included for illustrative purposes only.



Forth Crossing Bridge Constructors

uction VDV old
ight time VDV old for ntial dwellings
ared VDV
nt time VDV
gation Iber
bration data the vertical axis sented as this is f the vertical, dial vibration



- The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Springfield monitor on Sundays or during the Christmas period (21st December to 5th) ٠ of January).
- The PPV value on 19/12/13 has been investigated, and has been seen to be individual, isolated event within the period (see Vibrock PPV graph below), and is within the intermittent threshold of 10mm/s.





Forth Crossing Bridge Constructors

on PPV
hreshold ttent on
hreshold ous on
/DV PPV
PPV ion



The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Springfield monitor on Sundays or during the Christmas period (21st December to 5th) • of January).



Forth Crossing Bridge Constructors



• The grey areas of the chart represent the days on which no construction works were undertaken; no night time works were conducted in the vicinity of the Springfield vibration monitor throughout the month of December 2013. This graph is included for illustrative purposes only.



Forth Crossing Bridge Constructors

on VDV
time VDV for dwellings
VDV
ne VDV
on
ion data vertical axis ed as this is vertical, vibration



- The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted on 25th and 26th December 2013.
- The PPV values on 01/12/13, 15/12/13, 21/12/13, 27/12/13 & 29/12/13 have all been investigated, and have been seen to be individual, isolated events within the period (see Vibrock PPV graph below from 01/12/13), all but one • of which are within the intermittent threshold of 10mm/s. Furthermore, it is extremely unlikely that this particular level was generated as a result of FCBC construction, as the only works to be conducted in the vicinity of the monitor on this date was rebar, formwork & concreting works at the North Tower and drilling for de-stressing wells at Pier N1. None of these works involved the use of any vibration inducing plant and were a minimum of 180m (worst case) from the monitor.



Forth Crossing Bridge Constructors - A Joint Venture of Hochtief Solutions AG, American Bridge International, Dragados, S.A. and Galliford Try Infrastructure Limited (Trading as Morrison Construction)



Forth Crossing Bridge Constructors

on PPV S
hreshold ttent on
hreshold Ious Ion
/DV PPV
ion r
ion



• The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted on 25th and 26th December 2013.



Forth Crossing Bridge Constructors



Measured Night Time (23:00-07:00) Vibration Dose Values (VDV), Tigh-Na Grian,

Notes:

• The grey areas of the chart represent the days on which no construction works were undertaken; no night time works were conducted over the Christmas period (20th December to 5th January).



Forth Crossing Bridge Constructors



Measured highest Daily Peak Particle Velocity (PPV), Whinnyhill,

Notes:

- The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Whinnyhill monitor on Sundays or during the Christmas period (21st December to 5th) ٠ of January).
- The PPV values on 03/12/13 & 19/12/13 have been investigated, and have been seen to be individual, isolated events within each period (see Vibrock PPV graph below from 19/12/13), all of which are within the intermittent threshold of 10mm/s.



Forth Crossing Bridge Constructors - A Joint Venture of Hochtief Solutions AG, American Bridge International, Dragados, S.A. and Galliford Try Infrastructure Limited (Trading as Morrison Construction)



Forth Crossing Bridge Constructors

on PPV
hreshold ttent on
hreshold ous m
/DV PPV
on
on data ertical axis ed as this is vertical, vibration



• The grey areas of the chart represent the days on which no construction works were undertaken; no works were conducted in the vicinity of the Whinnyhill monitor on Sundays or during the Christmas period (21st December to 5th of January).



Forth Crossing Bridge Constructors



• The grey areas of the chart represent the days on which no construction works were undertaken; no night time works were conducted in the vicinity of the Whinnyhill vibration monitor throughout the month of December 2013. This graph is included for illustrative purposes only.



Forth Crossing Bridge Constructors

on VDV
time VDV for dwellings
VDV
me VDV
on
ion data vertical axis ed as this is e vertical, vibration