

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

CONTENTS	Page No.
1. WINTER SERVICE GENERAL	1
1.1 General	1
1.2 Winter Service Plan	1
1.3 Monitoring and Reporting	3
1.4 Basic Facility	4
2. WINTER SERVICE MANAGEMENT	5
2.1 Equipment and Services	5
2.2 Other Provisions	6
2.3 Winter Service Duty Officer	6
2.4 Decision Making Processes	7
2.5 Winter Service Exercises	7
2.6 Liaison and Communication	8
2.7 Winter Service Patrols	8
2.8 Airwave Communications	10
2.9 Areas Requiring Special Attention	10
2.10 Road Closures	10
2.11 Snow Fences, Shelter Belts and Snow Poles	12
2.12 Salt Bins	12
2.13 Hidden Message Signs	12
2.14 Records	13
3. WINTER SERVICE TREATMENTS	13
3.1 Precautionary Treatment	13
3.2 Response Times	15
3.3 Snow and Ice Clearance	15
4. OPERATING COMPANY'S WINTER SERVICE PLANT	18
4.1 General	18
4.2 Front line, Reserve, Additional and Loading Winter Service Plant	20
5. DE-ICING MATERIALS	21
5.1 General	21
5.2 Strategic Salt Stocks	22
5.3 Pre-wetted Salt	23
5.4 Alternative De-icing Materials	23
5.5 Abrasive Aggregates	23
5.6 Materials Storage	24
ANNEX 7.2/A – Winter Service Plan	25
ANNEX 7.2/B – Winter Service Report	33
ANNEX 7.2/C – Winter Service Patrols	37

ANNEX 7.2/D – Snow Clearance	41
ANNEX 7.2/E – Category A, B, C and D Footways, Footbridges and Cycling Facilities	45
ANNEX 7.2/F – Location of Known Areas Requiring Special Attention	59
ANNEX 7.2/G – Location Details	65
ANNEX 7.2/H – Records	73
ANNEX 7.2/I – Potassium Acetate Treatment	77
ANNEX 7.2/J – Appendices for Winter Service Plan	81
ANNEX 7.2/K – Requirements for De-Icing Material Spread Rates	89
ANNEX 7.2/L – Salt Stock Monitoring Report	95

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

1. WINTER SERVICE GENERAL

1.1 General

- 1.1.1 The Winter Service Period commences on 1 October and finishes on 15 May in each Annual Period.

During the Winter Service Period, the Operating Company shall prevent snow or ice from remaining on Trunk Roads in accordance with the requirements of this Part.

- 1.1.2 The Operating Company shall provide all resources, including depots (except where stated elsewhere in this Contract), materials, labour and Winter Service Plant to meet all winter weather conditions and deliver the level of Winter Service required to fulfil its obligations under this Contract.

- 1.1.3 The resources identified in Annex 7.2/J of this Part are the minimum provisions and shall not be construed as representing all resources required by the Operating Company to fulfil its obligations for the Winter Service.

- 1.1.4 The Operating Company shall ensure resources are available to provide and maintain the Winter Service if winter conditions occur outwith the Winter Service Period.

- 1.1.5 The Operating Company shall assist the Director in the preparation of an annual Winter Service publicity leaflet. Distribution in the first instance will be via Transport Scotland's website. However, the Operating Company shall carry out its distribution to:

- (i) filling stations,
- (ii) motorist service centres,
- (iii) motoring organisations,
- (iv) libraries, and
- (v) other public and private distribution outlets,

as required within the Unit.

- 1.1.6 Subject to an Order, the Operating Company shall execute Winter Service Operations in support of the Mutual Aid arrangements.

1.2 Winter Service Plan

- 1.2.1 The Operating Company's Winter Service Plan shall comprise the Operating Company's proposals and approach for delivering the Winter Service in any Winter Service Period to meet the requirements of this Contract.

- 1.2.2 The Operating Company's Winter Service Plan shall comply with the requirements of Transport Scotland's *Manual for the Management of the Risk of Unplanned Network Disruption* and be included within the Operating Company's Disruption Risk Management Plan as stated in Schedule 7 Part 3.

- 1.2.3 The Operating Company shall prepare its Winter Service Plan in accordance with the structure in Annex 7.2/A and include the details required by Annex 7.2/J of this Part.
- 1.2.4 The Operating Company shall also include the following details in its Winter Service Plan:
- (i) liaison arrangements to ensure the coordination of Winter Service Operations at the boundaries of the Unit,
 - (ii) arrangements for the management of strategic salt supplies,
 - (iii) Mutual Aid arrangements with other operating companies or local authorities,
 - (iv) its response times for mobilising Winter Service Plant and such other resources as shall be required to meet the requirements of this Part,
 - (v) rosters detailing the availability of all Operating Company staff required to provide the Winter Service throughout the Winter Service Period. The rosters shall include names, addresses and telephone numbers of the staff listed,
 - (vi) proposed arrangements for safe clearing of all roads within the Unit when they are covered in snow or ice,
 - (vii) the type, location and procedures for the operation of snow gates in each Winter Service Plan,
 - (viii) the arrangements for re-opening roads and snow gates within its Winter Service Plan, and
 - (ix) processes and procedures for deciding when it is unsafe to continue with, or commence, clearing Operations.
- 1.2.5 When preparing its Winter Service Plan, the Operating Company shall consult the Emergency Services, adjacent local authorities and their agents, other operating companies and other interested parties.
- 1.2.6 Not later than 30 days prior to the end of the Mobilisation Period, the Operating Company shall prepare and submit to the Director for his written consent, its Winter Service Plan for the period between the Commencement of Service Date and midnight on 15 May in the first Annual Period.
- 1.2.7 Prior to 31 July of each Annual Period, the Operating Company shall prepare and submit to the Director for written consent its Winter Service Plan for the forthcoming Winter Service Period.
- 1.2.8 Once consented to by the Director, the Operating Company's Winter Service Plan shall be incorporated into the Operating Company's Management System.
- 1.2.9 The Operating Company shall ensure its Winter Service Plan is kept under review prior to and during the Winter Service Period and any amendments required to accommodate changes in resource levels and the like shall be made. The Operating Company shall submit its amended Winter Service Plan to the Director for written consent. When consented to, the Operating Company's amended Winter Service Plan shall be incorporated into its Management System.

1.2.10 Prior to the commencement of each Winter Service Period, the Operating Company shall provide one controlled Electronic Copy of each approved Winter Service Plan to:

- (i) the Director,
- (ii) the Performance Audit Group,
- (iii) the Emergency Services,
- (iv) adjacent local authorities and their agents, and
- (v) other operating companies.

1.3 Monitoring and Reporting

1.3.1 The Operating Company shall support the Director in the operation of the Scottish Salt Group as required. For the purposes of this Part, the "Scottish Salt Group" includes representatives from the Society of Local Authority Chief Executives (SOLACE), the Society of Chief Officers of Transportation in Scotland (SCOTS), Convention of Scottish local Authorities (COSLA) and Transport Scotland. Its function is to monitor local authority and Trunk Road operator's salt returns, identify pressure points, arrange Mutual Aid, input to the United Kingdom Salt Cell, liaise with salt suppliers, provide salt conservation guidance, identify alternative salt suppliers and identify alternative de-icers.

1.3.2 The Operating Company shall provide the Director when requested with daily or weekly salt stock monitoring reports. Monthly salt stock monitoring reports shall be produced and submitted to the Director on the first Working Day of each month during the Winter Service Period.

Such reports shall detail salt stocks held, supply arrangement within the Unit, salt usage and include a position statement on salt stocks, actual and imminent salt orders and a forecast of forward usage. The salt stock monitoring report shall be in accordance with the structure shown in Annex 7.2/L of this Part.

1.3.3 No later than 31 May in each Annual Period, the Operating Company shall prepare a Winter Service Report on the Winter Service Plan and Winter Service Operations for the previous Winter Service Period, for review by the Director and the Performance Audit Group. The Winter Service Report shall help to inform the Director and the Operating Company about the improvements required for the next Winter Service Plan. The Winter Service Report shall be in accordance with the structure shown in Annex 7.2/B of this Part.

1.3.4 Prior to 31 May of the first Annual Period, the Operating Company shall prepare a Winter Service Report and submit it to the Director for the Winter Service Period ending 15 May in the first Annual Period.

1.3.5 To assist in the preparation of this Winter Service Report, prior to the Commencement of Service Date the Director shall provide the Operating Company with the Winter Service Plan prepared by the previous operating company and details of the Winter Service provided by it.

1.3.6 An annual review meeting between the Operating Company and the Director shall take place 10 Working Days after each annual Winter Service Report has been submitted to the Director, to consider the findings.

- 1.3.7 Prior to 31 May of the Final Annual Period, the outgoing Operating Company shall provide its Winter Service Plan and Winter Service Report for the final Winter Service Period to the Director to be passed to the incoming operating company.
- 1.3.8 During the Winter Service Period, the Operating Company shall produce daily reports on planned and actual treatments for each precautionary treatment route and each Winter Service Patrol route. These reports shall be recorded in an electronic format and shall include:
- (i) summary forecast and actual weather data,
 - (ii) planned and actual spread rates,
 - (iii) planned and actual commencement times,
 - (iv) completion times,
 - (v) amount of de-icing material spread and the cumulative amount spread during the current Winter Service Period,
 - (vi) plough usage,
 - (vii) number of treatment days (capability) of de-icing material available for each depot based on six treatments per route per day at 20 grammes per square metre,
 - (viii) the weather forecast accuracy, and
 - (ix) any other relevant information.

The Operating Company shall upload its daily report on planned treatments onto the Traffic Scotland website by 15:00 hours each day during the Winter Service Period.

For each operative, a log of hours spent on "call out" or "standby" shall be kept in accordance with the documented procedures in the Operating Company's Management System.

- 1.3.9 Throughout the Winter Service Period, a daily report shall be produced by the Operating Company. Such report shall be in an electronic format, agreed with the Director, based on information taken directly from the spreading vehicles' data logging and reporting system. The Operating Company shall upload the information onto the Traffic Scotland website by 15:00 hours each day.

1.4 Basic Facility

- 1.4.1 Operatives of Winter Service Plant shall hold current recognised qualifications and shall have the skills and experience to operate such Plant safely.
- 1.4.2 The Operating Company shall ensure that sufficient operatives shall be available at all times to provide the Winter Service Operations and to meet the required response times.
- 1.4.3 The Operating Company shall ensure that, throughout each Winter Service Period, sufficient trained operatives are available for each item of front line and reserve Winter Service Plant and each item of loading Winter Service Plant such that up to 24 hours per day working can be carried out.
- 1.4.4 The Operating Company shall ensure that, throughout the Winter Service Period, sufficient resources are available to minimise disruption to Winter Service

Operations caused by breakdown or any other similar circumstance and that Winter Service Operations are not delayed.

- 1.4.5 The Operating Company shall arrange for the necessary repairs to be carried out without delay unless such repair compromises delivery of the Winter Service, in which case the Operating Company shall mobilise the reserve Winter Service Plant to meet the required response times. The Operating Company shall ensure that repairs are carried out to main fleet vehicles without delay while the reserve fleet is operational.
- 1.4.6 A system that allows spoken communication with other Winter Service Plant operatives and the Winter Service Duty Officer shall be fitted in all Winter Service Plant. Such system shall be effective at all times and within all parts of the Unit including the location of the Winter Service Duty Officer.
- 1.4.7 Prior to 1 October in each Annual Period, the Operating Company shall:
- (i) drive the whole length of each precautionary treatment route in the Winter Service Plant to be used for the precautionary treatment of such route at speeds not exceeding those required for such precautionary treatment, and
 - (ii) fit and remove the plough to all Winter Service Plant so equipped,
- in order to ensure its operatives are familiar with the route and plant to be used.
- 1.4.8 Records of the requirements of paragraph 1.4.7 including details of:
- (i) time taken from depot to start of treatment route,
 - (ii) time taken to travel the route,
 - (iii) time taken to travel the treated route,
 - (iv) time taken to fit the plough,
 - (v) any problems encountered and actions taken to resolve them,
 - (vi) proposed longer term solutions to prevent recurrence of such problems, and
 - (vii) any other relevant information,
- shall be held electronically by the Operating Company in accordance with the documented procedures in its Management System.

2. WINTER SERVICE MANAGEMENT

2.1 Equipment and Services

- 2.1.1 The Operating Company shall provide the following to assist with its decision making process:
- (i) an expert weather forecasting service,
 - (ii) a computerised road weather information system including hardware, software and telecommunication links required to obtain, interpret and display as a minimum:
 - (a) road sensor data (forecast and actual),

- (b) historical thermal maps (where these are available, they shall be provided to the Operating Company by the Director but these will not be up to date),
- (c) weather data,
- (d) weather camera images, and
- (e) other relevant information,

in a manner that predicts trends in weather and road conditions.

- 2.1.2 The computerised road weather information system ("the system") shall be accessible to the expert weather forecasting service and shall be able to accept road sensors, mobile road sensors, alarms and action logs additional to those listed in Annex 7.2/G of this Part.

The Operating Company shall be responsible for the provision of everything within the system with the exception of road sensors, weather cameras and historical thermal maps.

No later than 30 days prior to the end of the Mobilisation Period, the Operating Company shall submit its proposed system to the Director for his written consent. If consent is not given, the Operating Company shall submit a revised system for approval within 10 Working Days of consent being refused.

- 2.1.3 The system shall have suitable computer terminals and software for the display of weather related radar information from the expert weather forecasting service. Such information shall be accessible to the Operating Company at all times during the Winter Service Period to assist in the Winter Service decision making process.

2.2 Other Provisions

- 2.2.1 The Operating Company shall provide and maintain all telecommunication links to meet the requirements of this Schedule.

- 2.2.2 All road sensors and weather prediction equipment shall use an open protocol based upon the Department for Transport *TR2020C* protocol.

Updated protocols may be used, but only where open access of the protocol is available to the Director to enable access to such protocol to other providers of equipment or service.

- 2.2.3 To obtain regular updates of road conditions, road sensors shall be polled by the Operating Company at intervals of 20 minutes between 1 October and 15 May and hourly at all other times. The Operating Company shall ensure that all cameras are operational throughout each Annual Period.

- 2.2.4 The Operating Company shall hold welfare kits and shall distribute these in the event of a Critical Incident as defined in Schedule 7 Part 3 which involves stranded vehicles. The welfare kits shall be carried by each Winter Service Patrol and shall as minimum include 24 space blankets, 24 bottles of water and 24 energy bars.

2.3 Winter Service Duty Officer

- 2.3.1 The Winter Service Duty Officer shall be authorised by the Operating Company to take decisions and to issue instructions on behalf of the Operating Company for implementing and directing the Winter Service and shall take such decisions and issue such instructions as are required. The Winter Service Duty Officer shall be on

duty in the control room whenever Winter Service Operations are planned. The Winter Service Duty Officer shall keep all Records relating to each decision made.

2.4 Decision Making Processes

2.4.1 During the Mobilisation Period, the Director shall provide road sensor data and historical thermal maps where available to the Operating Company.

2.4.2 During the Winter Service Period, the Operating Company shall monitor and interpret:

- (i) weather forecasts,
- (ii) Trunk Road conditions,
- (iii) data from road and mobile road sensors,
- (iv) the computerised road weather information system,
- (v) weather and Traffic Scotland cameras, and
- (vi) historical thermal maps when provided by the Director,

to ensure that the Winter Service Duty Officer receives and monitors climatic and road information to assist in the decision making process and in taking appropriate actions.

2.4.3 When snow or ice is forecast, action shall be taken by the Operating Company to keep the Trunk Roads in safe condition based, on its Winter Service Plan.

2.4.4 Following any precautionary treatment undertaken by the Operating Company, the Winter Service Duty Officer shall continue to monitor the weather forecasts and the actual weather conditions, including reports from Winter Service Patrols and data from the computerised road weather information system, to determine the ongoing effectiveness of the treatment and to instruct further treatment when this shall be required.

This shall be particularly important in situations where:

- (i) precipitation is forecast or has occurred that may reduce the effectiveness of a treatment, or
- (ii) the trend data from the computerised road weather information system changes from that predicted.

Where the information available to the Winter Service Duty Officer requires a review of the ongoing effectiveness of any precautionary treatment that has been undertaken, in terms of the ability of residual levels of de-icing material remaining on any pavement surface to deal with forecast or actual weather conditions, the Winter Service Duty Officer shall arrange for further precautionary treatment to be carried out.

2.5 Winter Service Exercises

2.5.1 The Operating Company shall carry out Winter Service "snow desk" exercises prior to 1 November of each Winter Service Period. Such exercises shall be based on scenarios provided by the Director and shall serve to test the effectiveness of the Operating Company's proposed Winter Service personnel.

2.5.2 The Operating Company shall assess its own performance and it shall also be assessed by the Director and the Performance Audit Group. In the event that the

performance is deemed unsatisfactory by any party, the Operating Company shall be required to take remedial action to improve demonstrably the effectiveness of the Winter Service personnel.

2.6 Liaison and Communication

2.6.1 During the Winter Service Period, the Operating Company shall report the known effects of such conditions to the Traffic Scotland Operator. The Operating Company shall liaise closely with:

- (i) Transport Scotland,
- (ii) the Police,
- (iii) the Traffic Scotland Operator,
- (iv) adjacent local road and road authorities, and
- (v) adjacent Trunk Road operators,

to monitor adverse winter weather and travelling conditions and ensure that its Winter Service Plan for provision of Winter Service at boundary interfaces is implemented.

2.6.2 When Winter Service Operations are planned, the Operating Company shall notify electronically, the organisations referred to in paragraph 2.6.1 of this Part, to inform them of such Operations and, when appropriate, to request that messages be displayed on all relevant electronic warning systems and variable message signs.

2.6.3 The Police may supply information to the media regarding Trunk Road travelling conditions during periods of Severe Weather.

2.7 Winter Service Patrols

2.7.1 From 1 November to 31 March inclusive, the Operating Company shall carry out Winter Service Patrols on those sections of Trunk Roads identified in Annex 7.2/C of this Part.

2.7.2 Category A and Category B Winter Service Patrols are identified in Annex 7.2/C of this Part.

2.7.3 All Winter Service Patrol vehicles shall comprise a pre-wet spreader with a minimum capacity of six cubic metres and with full functionality that meets the requirements of the Specification.

2.7.4 When the road surface temperature for any climatic area within a Winter Service Patrol route is forecast at any time to be less than, or equal to, three degrees centigrade, a Winter Service Patrol shall be enacted.

2.7.5 Winter Service Patrols shall:

- (i) patrol all carriageways of Trunk Roads, excluding slip roads,
- (ii) report on road conditions encountered to, and take instruction on treatments from, the Winter Service Duty Officer,
- (iii) provide an immediate response when instructed to carry out treatments or other de-icing Operations by the Winter Service Duty Officer,
- (iv) deal with any situation on the Winter Service Patrol route requiring immediate attention,

- (v) pay particular attention to the areas identified in Annex 7.2/F of this Part,
- (vi) undertake short stops for minor maintenance such as clearing grips and removing debris, and
- (vii) provide daily reports in the format indicated in Table 7.2.J.3 of Appendix WSP1 to Annex 7.2/J of this Part.

Where any situation on the Winter Service Patrol route cannot be resolved by any of the actions described in this paragraph, the Operating Company shall deploy additional resources to resolve the situation. Where any Incident occurs within the Unit, but outwith the Winter Service Patrol route, the Operating Company shall deploy additional resources to manage the Incident.

- 2.7.6 When, during a patrol, ice is found to have formed on a major Structure, the Operating Company shall use salt at the minimum rate specified in Table 7.2.K.4 of this Part as a spot treatment. If additional treatment is required, potassium acetate shall be used.
- 2.7.7 The Operating Company shall monitor the operation of Winter Service Patrols and take any action necessary to ensure that they comply with the requirements of this Part.
- 2.7.8 Winter Service Plant for Winter Service Patrols shall be fully loaded with de-icing material at the commencement of the Winter Service Patrol.
- 2.7.9 Category A Winter Service Patrols shall operate from 02:00hrs to 10:00hrs at two hourly intervals as described in paragraph 2.7.10 of this Part and shall be designed such that each Winter Service Patrol alternates between a one hour patrol and a one hour stand by on each route. All patrol routes shall be completed within one hour of commencement.
- The routes for a mix of dual and single carriageways shall be further designed so that the patrol vehicle, when working, is able to attend any location on its route within 45 minutes of receiving a call from the Winter Service Duty Officer.
- 2.7.10 Operating periods for Category A Winter Service Patrols shall be between 02:00hrs and 04:00hrs, 04:00hrs and 06:00hrs, 06:00hrs and 08:00hrs and 08:00hrs and 10:00hrs.
- 2.7.11 Category B Winter Service Patrols shall operate from 00:00hrs to 09:00hrs at three hourly intervals. Operating periods for Category B Winter Service Patrols shall be between 00:00hrs and 03:00hrs, 03:00hrs and 06:00hrs and 06:00hrs and 09:00hrs.
- 2.7.12 Winter Service Patrols shall allow for rest periods, patrolling both sides of dual carriageways and motorways and all actions required in accordance with paragraph 2.7.5 of this Part.
- 2.7.13 Winter Service Plant for Winter Service Patrols shall not be used by the Operating Company for undertaking precautionary treatments.
- 2.7.14 Winter Service Plant for Winter Service Patrols shall be used by the Operating Company for the clearance of snow or ice. Such usage shall only take place where it does not conflict with its primary function, or when the extent of the snowfall requires it to be used for snow clearing on the patrol route.

2.8 Airwave Communications

- 2.8.1 Category A and Category B Winter Service Patrols shall use an encrypted digital radio communications system known as Airwave. The Operating Company shall utilise this equipment as a dedicated communication system between Category A and Category B Winter Service Patrol personnel, the Traffic Scotland Control Centre, the Winter Service Duty Officer and the police.
- 2.8.2 In order to carry out the services required, the Operating Company shall be required to apply for, acquire and operate a TETRA Encryption Algorithm 2 sub-user licence for use with this communication system. The Operating Company shall be solely responsible for the procurement of, and conforming to any conditions of, this licence.
- 2.8.3 The Operating Company shall comply with the various codes of practice that apply to this type of licence. These codes, guidance on the Airwave sharers list and TETRA Encryption Algorithm 2 licensing are available from the Ofcom website at <http://licensing.ofcom.org.uk/radiocommunication-licences/business-radio/guidance-for-licensees/airwave-emergency-services/airwave/>.
- 2.8.4 The Operating Company shall develop an approved code of practice for the use of Airwave in compliance with Traffic Scotland Airwave Users Guide/Operating Protocols and Procedures.
- 2.8.5 The Operating Company shall indemnify the Director against any claims arising as a result of negligence or any other action on its part, relating to the use, storage and compliance of Airwave equipment and the Operating Company's TETRA Encryption Algorithm 2 sub-user licence.

2.9 Areas Requiring Special Attention

- 2.9.1 Areas requiring special attention are described in Annex 7.2/F of this Part and are areas where frost or ice is prone to occur, where water run-off is likely to happen or where the gradient is likely to affect the traction of vehicles.
- 2.9.2 The Operating Company shall review the areas requiring special attention referred to in Annex 7.2/F of this Part at least once in each Annual Period and amend the list as it considers necessary.

2.10 Road Closures

- 2.10.1 The Police are responsible for taking decisions to close roads during periods of adverse weather or road conditions.

When the Police, in consultation with the Operating Company, consider that the road is unsafe for vehicular traffic, the Operating Company shall arrange with the Police to close the road(s) and, if applicable, snow gates listed in Annex 7.2/G of this Part as considered necessary following such consultation.

- 2.10.2 The Operating Company shall liaise with the Police to establish and carry out procedures for the operation of snow gates, including checking that no vehicles or pedestrians are trapped on sections of Trunk Road between closed snow gates.

The procedures shall include:

- (i) manning the gates until a Police search of the road between the gates has been undertaken,

- (ii) securing the gates, having ascertained that no-one has been trapped between them,
- (iii) withdrawing all Operating Company personnel except those involved in the clearance of snow, and

agreeing the method of securing snow gates.

The Operating Company shall discuss and agree with the Police a standard type of padlock and suitable number of keys for the snow gates within the Unit. The Operating Company shall also agree with the Police on the number of keys to be held by each organisation. Two of the Operating Company's keys shall be held at the depot nearest to each snow gate. The Winter Service Duty Officer shall ensure that the keys are kept safely at all times and that they are returned to the depot in the event that they are taken out by the Operating Company in the course of its Winter Service Operations.

The Operating Company shall include the type, location and procedures for the operation of snow gates in each Winter Service Plan.

The Operating Company shall advise the Police when it considers that the road can be re-opened safely and shall arrange with the Police to re-open the road. The Operating Company shall document the arrangements for re-opening roads and snow gates within its Winter Service Plan.

- 2.10.3 When the Operating Company intends to close a snow gate, it shall immediately notify the Traffic Scotland Operator by telephone.
- 2.10.4 The Operating Company shall immediately notify the Traffic Scotland Operator by telephone following a Critical Incident which has caused or will cause significant disruption to traffic flow.
- 2.10.5 The Operating Company shall comply with the requirements of Schedule 7 Part 3 regarding notification of Critical Incidents to the Director and Performance Audit Group.
- 2.10.6 A written report shall be submitted to the Director by email within 12 hours of snow gates being closed due to snow or other adverse weather, giving details of:
 - (i) the reason for closing the gates,
 - (ii) the time that the gates were closed,
 - (iii) the time that the gates were re-opened or are likely to be re-opened,
 - (iv) any action to be taken prior to re-opening the gates,
 - (v) stranded motorists, if any, and
 - (vi) any other relevant information.
- 2.10.7 Following the closure of snow gates, snow clearing Operations shall continue on the section of Trunk Road between the gates as weather conditions permit, to allow the earliest possible re-opening of the Trunk Road.
- 2.10.8 The Operating Company shall inspect snow gates annually prior to the commencement of the Winter Service Period and shall, subject to an Order, undertake Operations to ensure they are functional and of effective appearance throughout the Winter Service Period.

2.11 Snow Fences, Shelter Belts and Snow Poles

- 2.11.1 The locations of existing snow fences and snow poles are provided in Annex 7.2/G of this Part.
- 2.11.2 During the first Annual Period, the Operating Company shall review the need for snow fences, shelter belts and snow poles on the Unit and, where it considers that alterations to existing provisions are necessary, the Operating Company shall make recommendations in writing for the Director's consent.
- 2.11.3 The Operating Company's recommendations for erection of additional snow fences, creation of additional shelter belts and erection of additional snow poles shall be included in each Winter Service Report.
- 2.11.4 On receipt of an Order, the Operating Company shall design and erect snow fences in accordance with the recommendations set out in Transport and Road Research Laboratory *Report LR 362 "Snow Fences"* by L E Hogbin dated January 1970, unless otherwise consented to in writing by the Director.
- 2.11.5 On receipt of an Order, the Operating Company shall supply and erect snow poles.
- 2.11.6 The Operating Company shall inspect snow fences and snow poles annually prior to the commencement of the Winter Service Period and shall, subject to an Order, undertake Operations to ensure they are functional and of effective appearance throughout the Winter Service Period.

2.12 Salt Bins

- 2.12.1 During each Winter Service Period, the Operating Company shall maintain as a minimum the salt bins at the locations stated in Annex 7.2/G of this Part.
- 2.12.2 The Operating Company shall review the current locations of salt bins and consider provision of additional locations to improve the Winter Service. It shall make appropriate recommendations in each Winter Service Report.
- 2.12.3 By 30 September each year, salt bins shall be provided and placed by the Operating Company at the locations identified in Annex 7.2/G of this Part. Throughout the Winter Service Period the Operating Company shall:
 - (i) replenish the salt bins with salt to ensure that a sufficient supply is always available for public use,
 - (ii) replace damaged, vandalised or missing salt bins within 48 hours of the damage, vandalism or absence becoming known by the Operating Company, and
 - (iii) at the end of each Winter Service Period, collect and take all salt bins to the Operating Company's depots for storage.

Before storage, the Operating Company shall empty and wash the salt bins and grease their hinges.

2.13 Hidden Message Signs

- 2.13.1 Hidden message signs are provided at the locations referred to in Annex 7.2/G of this Part.
- 2.13.2 The Operating Company shall open, or erect and open, snow or ice hidden message signs before the start of each Winter Service Period, or as conditions require, to

provide information for weather and road conditions during the Winter Service Period.

- 2.13.3 The Operating Company shall liaise with the Police to coordinate the activation of relevant signs when closing roads.

2.14 Records

- 2.14.1 The Operating Company shall complete and keep daily Records for Winter Service requirements as referred to in Annex 7.2/H of this Part. The Records shall be held electronically and have a remote access facility available to both the Director and the Performance Audit Group. The format of these Records shall be in accordance with the documented procedure in the Operating Company's Management System as it relates to the Winter Service. Data transmitted from the Winter Service Plant shall be received and stored in accordance with clause 2804AR of the Specification.

3. WINTER SERVICE TREATMENTS

3.1 Precautionary Treatment

- 3.1.1 The Operating Company shall undertake such precautionary treatment as is required.
- 3.1.2 The Winter Service Duty Officer shall instruct the commencement time and the spread rates for precautionary treatment Operations.
- 3.1.3 The total width of carriageway areas including:
- (i) slip roads,
 - (ii) hardshoulders,
 - (iii) hard strips,
 - (iv) turning Lanes,
 - (v) central reserve crossovers,
 - (vi) contiguous lay-bys,
 - (vii) bus bays,
 - (viii) cycle Lanes, and
 - (ix) hatched areas,
- shall receive precautionary treatments.
- 3.1.4 The Operating Company shall ensure that precautionary treatments for carriageways with negative texture surfaces shall be applied as close as is practical to the time road surface temperatures are forecast to be at less than, or equal to, plus one degree centigrade.
- 3.1.5 The Operating Company shall provide precautionary treatment for carriageways in the Unit when road surface temperatures fall, or are forecast to fall, to less than, or equal to, plus one degree centigrade or when snow conditions are forecast.
- 3.1.6 During precautionary treatments, all Winter Service Plant shall be driven in a manner appropriate to the prevailing weather conditions, and within the speed limit, but not exceeding 40 miles per hour.

- 3.1.7 On single carriageways, de-icing material shall be spread across the full width of the carriageway in a single pass.
- 3.1.8 A spreading vehicle shall not be used to treat a carriageway of more than three Lanes in a single pass. If the width of carriageway to receive de-icing treatment is greater than three Lanes, de-icing treatment shall be carried out either with two passes of the spreading vehicle or by the use of a second spreading vehicle.
- Spread patterns shall be adjusted to suit the carriageway width and the Lane in which the spreading vehicle is travelling.
- The completion times shall be in accordance with the required response times and shall be deemed to apply to the whole width of the carriageway.
- 3.1.9 Trunk Roads with temporary traffic management, including contra-flow running, may require the Operating Company to amend a treatment route.
- Particular care shall be taken by the Operating Company to ensure that all Lanes and contra-flow crossovers are adequately treated with de-icing material prior to removal of temporary traffic management and reopening to traffic.
- 3.1.10 Potassium acetate may be used as a precautionary treatment in specific circumstances, for example where Structures are susceptible to corrosion or when salt treatments are not fully effective (such as during extremely cold conditions).
- 3.1.11 Potassium acetate shall be applied at the locations specified in Annex 7.2/I of this Part including those parts of the Trunk Road 200 metres beyond the ends of each bridge.
- 3.1.12 The Operating Company shall monitor and manage variable road and weather conditions that may occur after precautionary treatments have been completed.
- 3.1.13 Precautionary treatment routes shall be designed to enable completion of treatment routes within two hours of commencement of the treatment in a single pass, except where the requirements detailed in paragraph 3.1.9 of this Part apply.
- 3.1.14 Precautionary treatments shall be carried out on Category A footways at locations identified in Annex 7.2/E of this Part when road surface temperatures are forecast to fall to less than, or equal to, plus one degree centigrade or when snow conditions are expected.
- 3.1.15 Precautionary treatment for footways, footbridges and cycling facilities shall be carried out as a separate Operation from carriageway precautionary treatments, utilising equipment suitable for the purpose.
- 3.1.16 The minimum spread rate for anti-icing materials for precautionary treatments to footways, footbridges and cycling facilities shall be 20 millilitres per square metre of brine with a minimum concentration of 20 percent. Actual treatment levels shall be discussed and agreed with the relevant local authorities.
- 3.1.17 The total width of footways, footbridges and cycling facilities shall be treated.
- 3.1.18 The Operating Company shall use pre-wetted salt in accordance with the Specification for precautionary de-icing treatments on all carriageway treatment routes in the Unit. Details of the Operating Company's proposals for such use shall be provided as shown in Table 7.2.J.4 of Appendix WSP2 to Annex 7.2/J of this Part and in each Winter Service Plan.

The Operating Company may, within its Winter Service Plan, propose the use of dry salt in accordance with the requirements of Table 7.2.K.2 of this Part to enable the effective de-icing of carriageway and footway treatment routes during certain weather conditions.

3.2 Response Times

- 3.2.1 Notwithstanding the requirements of paragraph 2.7 of this Part, when an immediate response is required for snow or ice clearance or other de-icing Operations, the Operating Company shall mobilise and commence its treatment within one hour of the Winter Service Duty Officer's decision.
- 3.2.2 When a planned response is required for precautionary treatment, the Operating Company shall mobilise and commence precautionary treatments to ensure completion before snow or ice conditions are predicted to occur, as indicated by the expert weather forecasting service.
- 3.2.3 For immediate or planned responses, the Operating Company shall complete treatment within two hours from the commencement of the treatment. Where normal access is prevented due to weather related or other Incidents, the Operating Company shall mobilise within one hour of becoming aware of the Incident and shall complete the precautionary treatment within three hours.
- 3.2.4 Cycling facilities within urban areas shall be considered Category C footways. The Operating Company shall identify such cycling facilities in each Winter Service Plan.
- 3.2.5 Category D footways, footbridges and cycleways are those not listed as being in Category A, B or C and shall receive treatment when required by the Director. The Operating Company shall identify Category D facilities in each Winter Service Plan.

3.3 Snow and Ice Clearance

- 3.3.1 Design of the ploughing route shall be in accordance with the requirements of Annex 7.2/D of this Part.
- 3.3.2 The Operating Company shall provide details in its Winter Service Plan of its ploughing routes in the form shown in Table 7.2.J.5 of Appendix WSP2 to Annex 7.2/J of this Part.
- 3.3.3 Spreading of de-icing materials during ploughing of carriageway areas shall be at the rate of spread instructed by the Winter Service Duty Officer.
- 3.3.4 The plough blade shall be set as close to the road surface as is consistent with the removal of the maximum amount of snow. The Operating Company shall ensure that the design of the plough blade allows for such use while preventing damage to the road surface, other equipment on the road surface and the plough blade.
- 3.3.5 The total width of carriageway as described in paragraph 3.1.3 of this Part shall be cleared of snow or ice.
- 3.3.6 In the event that treatment is required to lay-bys which are remote from the carriageway, this shall be the subject of an Order.
- 3.3.7 When planning and carrying out snow or ice clearance, the Operating Company shall pay particular attention to the layout of the carriageway in terms of the overall number of Lanes and the location of entrance and exit slip Lanes.

Snow or ice clearance of slip roads shall be coordinated with main carriageway clearance.

A clear path shall be kept open between those entry and exit points where frequent Lane changes are necessary.

3.3.8 On dual carriageway and multi-Lane motorway Trunk Roads:

- (i) the Operating Company shall use echelon ploughing to clear the carriageway when required,
- (ii) echelon ploughing shall be undertaken by two or more vehicles, a minimum of one of which shall be front line Winter Service Plant, all moving in the same direction, one behind each other, on adjacent Lanes,
- (iii) only the right hand Lane may be ploughed towards the central reservation,
- (iv) irregular windrows caused by ploughing passes, especially those which weave from one Lane to another, shall be avoided,
- (v) Lanes shall be completely cleared and the windrows of snow remaining shall form a smooth and continuous line without sudden encroachments into the cleared path,
- (vi) windrows may be temporarily left on hard shoulders but these shall be cleared as soon as road surface conditions on running Lanes are safe, and
- (vii) clearance work shall proceed continuously until no snow remains on the carriageway.

During and after prolonged falls of snow, ploughing shall be used continuously from the onset of snow to prevent snow build up and compaction by traffic and to ensure the snow clearance of all Trunk Roads.

Such ploughing shall be supplemented by simultaneous de-icing treatment at a minimum spread rate of 20 grammes per square metre.

3.3.9 If the road surface temperature continues to fall and the need for ploughing continues, or hard packed snow or ice has formed, the spread rate shall be increased as necessary to a maximum rate of 40 grammes per square metre in accordance with the requirements in Table 7.2.K.2 of Annex 7.2/K of this Part.

3.3.10 Where conventional ploughing is not possible, for example:

- (i) in built up areas,
- (ii) in exceptional circumstances when the snow on the road is deep and cannot be removed,
- (iii) when de-icing treatment over packed snow is likely to provide an unacceptable surface,
- (iv) when the traffic is insufficient to disperse the snow, or
- (v) through certain traffic management conditions,

the Operating Company shall carry out Operations to lift, remove and dispose of snow or ice, or utilise snow blowers with the snow being directed onto adjacent land where the Operating Company has obtained the prior agreement of the landowner and the Scottish Environmental Protection Agency.

Such Operations shall be followed by de-icing treatment.

3.3.11 Where there is a formation of hard packed snow or ice not exceeding 20 millimetres thickness and the air temperature is above minus five degrees centigrade, removal shall be achieved by using successive spreading of de-icing material in accordance with Table 7.2.K.2 in Annex 7.2/K of this Part.

3.3.12 Where there is a formation of hard packed snow or ice:

- (i) not exceeding 20 millimetres thickness and air temperature is less than, or equal to, minus five degrees centigrade, or
- (ii) exceeding 20 millimetres thickness,

the addition of abrasive aggregates shall be considered in accordance with paragraph 5.5 of this Part. Application of the initial treatment technique should be resumed as soon as possible since abrasives contribute little to the removal of snow or ice and may block drains and gullies upon thawing. Abrasives shall not be used on Structures where there is any danger of blockage to drains.

Abrasive aggregates may be used by the Operating Company as a supplement in urban areas where de-icing material alone would provide an unacceptably slippery surface.

3.3.13 Footway, footbridge and cycleway categories and the response times and clearance requirements for each category are provided in Tables 7.2.E.1 and 7.2.E.2 in Annex 7.2/E of this Part. Table 7.2.E.3 provides details of such Structures within the Unit. The Operating Company shall ensure Table 7.2.E.3 is kept up to date during the Contract Period and shall make written proposals for the inclusion and treatment of additional footways, footbridges and cycleways for the Director's consent.

3.3.14 Following clearance of snow or ice from footways, footbridges and cycling facilities, de-icing material shall be spread in accordance with paragraph 3.1.17. Where snow or ice remains on footways, footbridges and cycling facilities after treatment, de-icing material shall be spread at a minimum spread rate of 20 grammes per square metre, or as specified in Table 7.2.K.2 of Annex 7.2/K of this Part as appropriate, to prevent ice formation on the cleared surfaces.

The full width of the footways, footbridges and cycling facilities shall be treated.

3.3.15 The Operating Company shall, in discussion with Network Rail or any successor organisation, ensure that appropriate safety precautions are taken when snow ploughing vehicles are negotiating railway level crossings.

When snowploughing or snow blowing Operations are undertaken, the Operating Company shall ensure that snow or ice does not build up across or against:

- (i) railway tracks,
- (ii) gates,
- (iii) bridge parapets,
- (iv) fences,
- (v) walls, and
- (vi) other boundaries.

Where snow or ice clearance is carried out adjacent to railway overhead electricity cables, the Operating Company shall take special care to ensure snow does not cause electrical short circuits or other damage.

- 3.3.16 During prolonged periods of snow fall at locations where the use of salt for de-icing is prohibited, ploughing shall be continuous followed by repeated applications of de-icing chemical.

- 3.3.17 Lifting and removal of snow or ice from multi-level and grade separated interchanges and other locations shall be undertaken where necessary.

Sites for the disposal of snow or ice arising from such Operations shall comply with the requirement of the Scottish Environmental Protection Agency.

The Operating Company shall provide temporary traffic management, including road closures, where required for these Operations.

- 3.3.18 When ploughing to the nearside, other vehicles (unless stationary or on the hard-shoulder) shall not be overtaken. Snow or ice shall not be thrown over bridge parapets onto the road beneath. When ploughing to the central reservation, the speed used shall prevent the throwing of snow or ice into the path of traffic on the opposite carriageway.

- 3.3.19 In the event of significant snow falls, where snow ploughing being carried out by the front line and reserve Winter Service Plant is not sufficient, the Operating Company shall deploy additional Winter Service Plant for snow clearance to ensure delays caused by the weather conditions are kept to a minimum.

- 3.3.20 When machine snow clearance is not suitable (including clearance around carriageway obstructions) hand snow clearance and salting shall be carried out.

- 3.3.21 Snow or ice shall be cleared in a manner that prevents it from landing on adjacent or underlying paved surfaces.

4. OPERATING COMPANY'S WINTER SERVICE PLANT

4.1 General

- 4.1.1 Annex 7.2/J of this Part details the minimum Winter Service Plant to be used in connection with the Winter Service. The Operating Company shall provide and ensure that the Winter Service Plant listed in Annex 7.2/J of this Part is available as necessary for the Winter Service.

- 4.1.2 The Operating Company shall ensure that its Winter Service Plant is maintained in accordance with manufacturers' recommendations.

In the event of a breakdown on any of the Operating Company's front line Winter Service Plant:

- (i) details of the cause, time and location of the breakdown and any other relevant information shall be recorded,
- (ii) the operator shall, if possible, return the vehicle to the nearest depot in order to minimise blockages and further disruption to the network, and
- (iii) the Operating Company shall make immediate arrangements for reserve Winter Service Plant to be made available in order to comply with the requirements of this Part.

- 4.1.3 When used on the Trunk Road for operative training and maintenance runs, the spinner disc at the rear of the Operating Company's Winter Service Plant shall be covered in such a way that damage caused by sharp edges in the event of an accident is reduced to a minimum.
- 4.1.4 Front line and reserve Winter Service Plant shall be fitted with on-board electronic data loggers in accordance with the requirements of clause 2803AR of the Specification.
- 4.1.5 The onboard electronic data loggers shall be capable of transmitting their data in near real time to a web accessible database in accordance with the requirements of clause 2804AR of the Specification.
- In the event of an on board electronic data logger malfunction, the Operating Company shall prepare a similar written record within 12 hours.
- 4.1.6 The Operating Company shall measure and record the quantity of de-icing material spread on each occasion on each precautionary treatment route. Such apparatus shall either be fitted to Winter Service Plant or located at depots and shall be additional to the data loggers.
- 4.1.7 In September and January of each Annual Period, the Operating Company shall calibrate all equipment for spreading de-icing material:
- (i) in accordance with the requirements of British Standard 1622:1989, or
 - (ii) where British Standard 1622:1989 does not provide for the calibration of any de-icing spreading equipment, in a manner proposed in writing by the Operating Company and consented to in writing by the Director. As a minimum the Operating Company shall provide details of the Winter Service Plant supplier's calibration method to the Director, and
 - (iii) in accordance with the requirements of the specific material being used.
- 4.1.8 September testing shall comply with the requirements of tests 'A' and 'B' and January testing shall comply with the requirements of test 'B' of British Standard 1622:1989.
- 4.1.9 Re-calibration and testing shall be carried out after repairs to the spreading equipment and at other times when necessary to ensure the accuracy of de-icing material spreading.
- All calibration and re-calibration shall be independently carried out and certified. Calibration certificates shall be held in accordance with the requirements of the Winter Service Plan and the Operating Company's Management System.
- 4.1.10 The Winter Service Plant that is used for spreading de-icing materials on the Trunk Roads shall be of sufficient capacity to enable the Operating Company to fulfil its obligations for Winter Service Operations.
- 4.1.11 Winter Service Plant used for spreading pre-wetted salt shall:
- (i) be capable of delivering a constant supply of brine of the appropriate concentration in accordance with paragraph 5.3.5 of this Part,
 - (ii) comply with the requirements of this Part where such requirements are not inconsistent with the spreading of pre-wetted salt, and

- (iii) comply with any other requirements to ensure the effective distribution of pre-wetted salt to comply with the requirements of this Part.

The Operating Company shall demonstrate to the Director that the brine delivery system of the Winter Service Plant used for spreading pre-wetted salt meets all the requirements of this Part and the Operating Company shall provide in writing to the Director the method that will be employed to ensure that the quantity of the brine being applied during each route treatment is correct.

- 4.1.12 Winter Service Plant used shall comply with the requirements of this Part to ensure the effective distribution of potassium acetate and other de-icing materials.

- 4.1.13 The Operating Company shall provide a range of snowploughs or other winter service plant that is capable of clearing all snow conditions on all carriageway routes, footways, footbridges and cycleways in the Unit.

- 4.1.14 Snow blowers shall:

- (i) be capable of blowing up to 600 tonnes of snow per hour,
- (ii) have a width of cutter head of at least 1.8 metres,
- (iii) be capable of operating in up to four metres depth of snow, and
- (iv) be fitted with lights to permit effective operation during poor visibility and the hours of darkness.

- 4.1.15 All Winter Service Plant used for Winter Service Operations shall:

- (i) comply with the requirements of this Part,
- (ii) be fitted with a snowplough, and
- (iii) have a minimum of two additional headlamps fitted to permit forward visibility when a snow plough is fitted.

4.2 Front line, Reserve, Additional and Loading Winter Service Plant

- 4.2.1 The Operating Company's minimum front line, reserve and additional Winter Service Plant available for the Winter Service shall be as referred to in Appendix WSP4 to Annex 7.2/J of this Part. The minimum loading Winter Service Plant available within the Unit for loading front line, reserve and additional Winter Service Plant shall also be as referred to in Appendix WSP4.

- 4.2.2 Front line Winter Service Plant comprises vehicles and equipment permanently available within the Unit that is required for:

- (i) precautionary treatments,
- (ii) snow or ice clearance to a fallen or formed depth not exceeding 100 millimetres, but excluding Winter Service Plant not required to be capable of spreading whilst echelon ploughing,
- (iii) Winter Service Patrols, and
- (iv) compliance with the requirements of this Part.

- 4.2.3 All front line Winter Service Plant shall be fitted with measuring devices for air temperature and road surface temperature which shall be capable of transmitting data to the on-board data logging system.

4.2.4 Front line Winter Service Plant shall, as a minimum, have the ability to:

- (i) carry out precautionary treatment to all routes simultaneously,
- (ii) carry out Winter Service Patrols on Category A and B routes,
- (iii) clear ice and snow lying to a depth up to 100 millimetres, and
- (iv) spread pre-wetted salt.

4.2.5 The Operating Company's reserve Winter Service Plant shall be that part of the Winter Service Plant permanently available within the Unit to supplement front line Winter Service Plant for the Winter Service in situations:

- (i) when such front line Winter Service Plant may not be available for whatever reason for the Winter Service, or
- (ii) to clear snow or ice in accordance with the requirements of this Part.

The reserve Winter Service Plant may also be used to supplement front line Winter Service Plant in snow conditions.

4.2.6 The additional Winter Service Plant shall be that part of the Winter Service Plant that is available for the Winter Service, either directly under the control of the Operating Company or through contingency arrangements with third parties, to deal with:

- (i) snow or ice lying to a depth of more than 100 millimetres, and
- (ii) any other winter weather conditions which cannot be managed by front line or reserve Winter Service Plant.

4.2.7 Details of additional Winter Service Plant shall be as referred to in Appendix WSP4 to Annex 7.2/J of this Part.

5. DE-ICING MATERIALS

5.1 General

5.1.1 The Operating Company shall procure and provide the salt and other de-icing materials necessary to comply with the Winter Service requirements.

5.1.2 The Operating Company shall provide the minimum operational salt stock levels at the start of the Winter Service Period as detailed in Appendix WSP3 to Annex 7.2/J of this Part. If stocks have reduced to 90 percent on 21 December in any Winter Service Period, the Operating Company shall restock to 100 percent of the full pre-season stocks.

5.1.3 Salt for de-icing shall be 6.3 millimetre grading particle size complying with British Standard 3247:1991 and treated with an anti-caking agent.

5.1.4 The method of salt storage at loading points shall ensure that the moisture content of the stored salt does not exceed four percent. Should the moisture content of salt exceed four percent, the Operating Company shall take all measures necessary to ensure compliance with the requirements of this Part is regained.

Where moisture content is deliberately increased to deal with low humidity conditions, the spread rate shall not be increased.

- 5.1.5 Within 10 Working Days of each delivery, salt shall be tested by the Operating Company at loading points in accordance with British Standard 3247:1991 and results recorded to ascertain:
- (i) moisture content (one test per 500 tonnes),
 - (ii) particle size distribution (one test per 500 tonnes),
 - (iii) chloride content (one test per 1500 tonnes), and
 - (iv) soluble sulphate compounds (one test per 1500 tonnes).
- 5.1.6 Salt stocks shall be tested by the Operating Company for salt moisture content at monthly intervals throughout each Winter Service Period and the results shall be recorded. As a minimum, the salt should be tested at the base, centre and top of the stockpile.
- 5.1.7 The Operating Company shall store materials test data on an electronic database.
- 5.1.8 Potassium Acetate used for de-icing Operations at the locations specified in Table 7.2.I.1 of Annex 7.2/I shall comply with the Ministry of Defence Specification 68-118 (De-icing/Anti-Icing Fluid for Run Ways) unless otherwise consented to in writing by the Director.

5.2 Strategic Salt Stocks

- 5.2.1 Subject to an Order, the Operating Company shall procure and store strategic salt stocks when instructed by the Director.
- 5.2.2 The Operating Company shall provide storage facilities capable of storing 25,000 tonnes of strategic salt. Storage shall be in accordance with the requirements of paragraph 5.6 of this Part.
- 5.2.3 In undertaking these duties the Operating Company shall:
- (i) seek prices from all salt suppliers to ensure value for money,
 - (ii) manage and maintain the strategic salt stocks on behalf of the Director including accurate stock monitoring using an approved weigh bridge facility,
 - (iii) arrange haulage of strategic salt stocks from the initial delivery point to the strategic salt depot(s),
 - (iv) maintain accurate Records of quantities and their locations,
 - (v) undertake stock rotation to avoid deterioration of the salt,
 - (vi) liaise with all relevant third parties such as local authorities to ascertain their need for supplies of strategic salt,
 - (vii) make arrangements with such third parties for loading and haulage of, and 24 hours a day, seven days a week access to, the strategic salt, and
 - (viii) invoice such third parties for all costs related to provision of strategic salt stocks on behalf of the Director.
- 5.2.4 All invoice information shall be entered into the contract control and management function of the Integrated Roads Information System as either a credit or debit as appropriate.
- 5.2.5 The Operating Company shall transfer strategic salt stocks which have not been utilised at the end of the Winter Service Period into its operational salt stocks for use

in the next Winter Service Period. Subject to an Order, the Operating Company shall procure new strategic salt stocks to replace such transferred stock.

5.3 Pre-wetted Salt

5.3.1 Salt for de-icing material as part of pre-wetted salt Operations, not including the salt to be used in producing brine, shall be 6.3 millimetre grading particle size complying with British Standard 3247:1991 or equivalent.

5.3.2 Salt for de-icing material as part of pre-wetted salt Operations to be used in producing brine shall be suitable for such production.

5.3.3 For pre-wetted salt spreading Operations, the spread rates set out in Table 7.2.K.2 of Annex 7.2/K of this Part shall represent the total weight of the spread material.

5.3.4 Brine added to salt during spreading Operations shall comprise 30 percent of the total spread material by weight, giving a 70 percent salt: 30 percent brine solution.

5.3.5 Brine solution with a concentration of 23 percent dissolved sodium chloride shall be used as the pre-wetting agent.

Where air temperatures are forecast to fall below minus 15 degrees centigrade, the brine shall be diluted by the addition of five percent to ten percent water to prevent re-crystallisation of the salt. The addition of water shall be undertaken in a manner which ensures that the water and brine is thoroughly mixed to produce a consistent concentration of brine.

5.3.6 The Operating Company shall arrange for sufficient brine to be stored at each depot to treat simultaneously, at a maximum spread rate, all precautionary treatment routes serviced from that depot. An additional quantity of 20 percent brine above the minimum shall be held in reserve.

The brine within the storage facilities shall be replenished within two hours of being depleted.

5.3.7 Sensors with digital read outs shall be fitted to the Operating Company's storage facilities to measure the salt concentration of the brine automatically.

Daily checks shall be carried out by the Operating Company using a saturation meter and the results shall be stored electronically. Water supplies to saturator units shall be protected from freezing by appropriate measures.

5.4 Alternative De-icing Materials

5.4.1 In extreme conditions, such as when temperatures drop below levels at which sodium chloride is effective, the Operating Company shall use alternative de-icing materials in accordance with guidance on use of such materials, to be provided by the Director and subject to his written consent. Such alternative de-icing material shall be described in the Operating Company's Winter Service Plan.

5.4.2 The Operating Company shall store 15,000 litres, or equivalent, of alternative de-icing material within the Unit to deliver the requirements of paragraph 5.4.1 of this Part.

5.5 Abrasive Aggregates

5.5.1 A single sized abrasive aggregate with particle size of six millimetres, or five millimetres sharp sand having low fines content, shall be added to the salt in a 50

percent salt: 50 percent abrasive aggregate or sand mixture in accordance with the requirements of this Part.

5.6 Materials Storage

- 5.6.1 Materials shall be stored in a covered structure within the Operating Company's depots to ensure compliance with the requirements of this Part and the supplier's written instructions in the case of additives, potassium acetate and any other de-icing materials.
- 5.6.2 The Operating Company shall satisfy itself that arrangements for storage, handling and loading of de-icing materials at the loading points are adequate to achieve the specified response times.
- 5.6.3 Where there is no provision for covered storage at the Commencement of Service Date, the Operating Company shall provide such storage no later than 12 months after the Commencement of Service Date. Prior to the provision of such storage, all salt stored externally shall be covered in protective sheeting in a manner that prevents the ingress of moisture into the material as far as is practicable. All salt stored in a covered structure shall be rotated on a weekly basis to maintain a uniform condition.
- 5.6.4 As salt de-icing material is removed from storage areas by the Operating Company, a positive slope shall be maintained to avoid danger to operatives and Winter Service Plant from the collapse of faces of stockpiles.
- 5.6.5 The Operating Company shall safeguard and manage all de-icing material stock and storage facilities.
- 5.6.6 The Operating Company shall ensure that de-icing material stock does not become contaminated with foreign matter likely to cause damage to Winter Service Plant, cause the de-icing material to fail to comply with the requirements of this Part or adversely affect Trunk Road users.

This is Annex 7.2/A to Schedule 7 Part 2 referred to in the foregoing Agreement between Scottish Ministers and BEAR Scotland Limited.

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/A – Winter Service Plan

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/A – Winter Service Plan

1. MANAGEMENT ARRANGEMENTS

The Winter Service Plan shall provide the following details:

1.1 Winter Service Manager

- 1.1.1 Name,
- 1.1.2 Qualifications,
- 1.1.3 Experience,
- 1.1.4 Responsibilities.

1.2 Winter Service Duty Officers

- 1.2.1 Names,
- 1.2.2 Qualifications,
- 1.2.3 Experience,
- 1.2.4 Responsibilities.

1.3 Monitoring Arrangements

- 1.3.1 Monitoring arrangements during normal working hours,
- 1.3.2 Monitoring arrangements outwith normal working hours.

1.4 Personnel Resources

- 1.4.1 Names of staff and labour resources,
- 1.4.2 Availability rosters including names, addresses and telephone numbers of the staff listed.

1.5 Call out arrangements

- 1.5.1 Call out arrangements during normal working hours,
- 1.5.2 Call out arrangements outwith normal working hours,
- 1.5.3 Contact arrangements during normal working hours,
- 1.5.4 Contact arrangements outwith normal working hours,
- 1.5.5 Mobilisation times.

1.6 Communications Equipment

1.7 Training for Managers and Other Staff

- 1.7.1 Details of previous training,
- 1.7.2 Details of proposed training.

2. WEATHER FORECASTING

2.1 Purpose

2.2 Methodology

2.3 Weather forecasting service

2.3.1 Climatic domains,

2.3.2 Weather radar,

2.3.3 Ice sensors and weather forecast sites,

2.3.4 Thermal mapping,

2.3.5 Location plans.

2.4 Computer Systems

3. MONITORING ARRANGEMENTS FOR AREAS REQUIRING SPECIAL ATTENTION

4. DECISION MAKING

4.1 Role of the Winter Service Manager

4.2 Role of the Winter Service Duty Officer

4.2.1 Winter Service Patrol mobilisation,

4.2.2 Proposals for precautionary and additional de-icing treatments when low confidence forecasts are issued for variable road and weather conditions,

4.2.3 Proposals for monitoring the effectiveness of de-icing materials,

4.2.4 Road closure and snow gate operational procedures,

4.2.5 Activation of hidden message signs.

5. LIAISON

5.1.1 Liaison with:

(i) the Director,

(ii) the Police,

(iii) the Traffic Scotland Operator,

(iv) adjacent road and highway authorities,

(v) adjacent Trunk Road operating companies including DBFO's, and

(vi) Network Rail.

6. MUTUAL AID ARRANGEMENTS

6.1 Mutual Aid

6.1.1 A statement explaining what Mutual Aid arrangements are in place, including contact details.

7. WINTER SERVICE PATROLS

7.1 Winter Service Plant and Reporting

- 7.1.1 Winter Service Plant provided by the Operating Company for the Winter Service Patrols shall be as referred to in Appendix WSP1 to Annex 7.2/J of this Part.
- 7.1.2 A Winter Service Patrol Report shall be provided by the Operating Company in the format referred to in Appendix WSP1 to Annex 7.2/J of this Part.

8. TREATMENT ROUTES

- 8.1.1 The Operating Company shall provide the following information in Appendix WSP2 to Annex 7.2/J of this Part:
 - (i) precautionary treatment routes, including sections shared with an adjacent road authority,
 - (ii) contingency plans for alternative access to precautionary treatment routes where normal access is prevented due to weather related or other incidents, and
 - (iii) locations of de-icing material loading points.
- 8.1.2 The Operating Company shall provide details of cycling facilities in urban areas in Appendix WSP2 to Annex 7.2/J of this Part.

9. SNOW AND ICE CLEARANCE

9.1 Snow Clearing

- 9.1.1 Description of arrangements (including ploughing plans) and resources for managing snowfall. This plan shall demonstrate that all available ploughing plant is fully utilised to ensure that all carriageways are maintained free from snow or ice.
- 9.1.2 Road closure procedure including use of snow gates.
- 9.1.3 Prolonged snowfall strategy, including use of additional Winter Service Plant and operative resources.
- 9.1.4 Arrangements for safe clearance of snow or ice from wide single carriageways.
- 9.1.5 Arrangements for safe clearance of snow or ice adjacent to vertical concrete barriers.
- 9.1.6 Treatment strategy for footways, footpaths and cycling facilities including location of salt bins where applicable.
- 9.2 Plans showing the location of the footways, footbridges and cycling facilities in Categories A, B, C and D.

10. DE-ICING MATERIALS

10.1 Details

- 10.1.1 For each type of de-icing material, including alternatives:
 - (i) detailed specification of material,
 - (ii) storage conditions, system types and capacities,

- (iii) details on testing methods, including their type and frequency,
- (iv) state suppliers, including any secondary suppliers,
- (v) state any importers used to meet supply demands,
- (vi) stock levels (total and split by location), and
- (vii) details of re-stocking, including procurement mechanism and details of stock level monitoring.

10.1.2 Details of de-icing materials stocks shall be provided by the Operating Company in Appendix WSP3 to Annex 7.2/J of this Part and shall take account of the minimum stock levels to be maintained as referred to in the Appendix.

11. STRATEGIC SALT STOCKS

11.1 Details

- 11.1.1 Identification of suppliers including locations, initial delivery points and haulage arrangements.
- 11.1.2 Identification of Operating Company storage facilities.
- 11.1.3 Identification of third parties, liaison arrangements, haulage, delivery and 24 hour access arrangements.

12. WINTER SERVICE PLANT

- 12.1.1 The Operating Company's front line Winter Service Plant and reserve Winter Service Plant available within the Unit for the Winter Service shall be provided by the Operating Company in Appendix WSP4 to Annex 7.2/J of this Part.
- 12.1.2 The Operating Company's additional Winter Service Plant available through contingency arrangements and arrangements for its mobilisation for the Winter Service shall be provided by the Operating Company in Appendix WSP4 to Annex 7.2/J of this Part.
- 12.1.3 Loading Winter Service Plant available within the Unit for loading such front line, reserve and additional Winter Service Plant shall be provided by the Operating Company in Appendix WSP4 to Annex 7.2/J of this Part.
- 12.2 **Calibration of Winter Service Plant**
 - 12.2.1 Calibration arrangements and procedures for front line and reserve Winter Service Plant, in accordance with paragraphs 4.1.7, 4.1.8 and 4.1.9 of this Part.
 - 12.2.2 The Winter Service Plan will describe how the requirements of this Part shall be met and where and how the calibration certificates will be held.

13. COMPOUNDS, DEPOTS AND FACILITIES

- 13.1 A schedule of compounds, depots and facilities covering the network within the Unit shall be provided by the Operating Company in Appendix WSP5 to Annex 7.2/J of this Part.

14. MAPS DRAWINGS AND GRAPHICAL INFORMATION

14.1 Maps

14.1.1 Provide scale maps for the following:

- (i) precautionary treatment routes for carriageways, including on/off slips and depots,
- (ii) precautionary treatment routes for footways, footbridges and cycling facilities,
- (iii) reactive treatment routes for footways, footbridges and cycling facilities,
- (iv) Winter Service Patrol routes,
- (v) ploughing routes for carriageways, including on/off slips and depots,
- (vi) road sensors including sensor types and where these sites are equipped with weather cameras, (map to differentiate between single and bi-directional cameras),
- (vii) snow gates,
- (viii) snow fences,
- (ix) shelter belts,
- (x) snow poles,
- (xi) snow or ice and hidden message signs,
- (xii) salt bins,
- (xiii) vertical concrete barriers,
- (xiv) other facilities, and
- (xv) where route based forecasting is not used, climatic domains and the sensors used to generate domain forecasts.

15. COMPILING AND MAINTAINING RECORDS

16. SNOW POLES

- 16.1 Maintenance, replacement of damaged or missing snow poles, refurbishment and reserve stocks.

17. SNOW GATES

- 17.1 Maintenance, operation and liaison.

18. VARIABLE MESSAGE SNOW AND ICE AND HIDDEN MESSAGE SIGNS

- 18.1 Operating and liaison procedures.

19. SALT BINS

- 19.1 Stock level monitoring and replenishment procedures.

20. SALT MEASUREMENT APPARATUS

20.1 Equipment and locations and recording methods.

This is Annex 7.2/B to Schedule 7 Part 2 referred to in the foregoing Agreement between Scottish Ministers and BEAR Scotland Limited.

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/B – Winter Service Report

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/B – Winter Service Report

- 1 The Winter Service report shall provide:
 - 1.1 An executive summary of the annual report.
 - 1.2 An overview and review of the service provided.
 - 1.3 A summary of key performance reports.
 - 1.4 Information on significant events and related actions.
 - 1.5 An assessment of the accuracy of weather forecasts provided.
 - 1.6 An assessment of road sensor performance.
 - 1.7 An analysis of the ability of the Management System to capture reported Non-Conformances.
 - 1.8 Details of innovations and improvements implemented.
 - 1.9 Recommendations for continuous improvement.
 - 1.10 Details of actions taken during periods of low confidence forecasting for variable and marginal winter weather conditions.
 - 1.11 Details of Winter Service Plant available, including reserve and additional Winter Service Plant.

This is Annex 7.2/C to Schedule 7 Part 2 referred to in the foregoing Agreement between Scottish Ministers and BEAR Scotland Limited.

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/C – Winter Service Patrols

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/C – Winter Service Patrols

1. The Category A and B Winter Service Patrols are provided in Table 7.2.C.1.

Table 7.2.C.1 – Category A and B Winter Service Patrol Routes

North West Unit	
Route	Category
A9 Inverness from Longman Roundabout to Perth at Inveralmond Roundabout	A
A9 Brora to Thurso (ferry port)	B
A835 Contin to Ullapool (ferry port)	B
A82 Fort William (Lochybridge) to Inverness (Tomnahurich)	B
A85 Oban to Tyndrum	B
A85 Lochearnhead to Crianlarich	B
A82 Ballachulish to Tarbet	B
A87 Invergarry to Shiel Bridge	B
A887 Bunloyne to Invermoriston	B
A83 Inveraray to Tarbet	B

2. Details of the Operating Company's Winter Service Patrol routes shall be as provided by the Operating Company in Table 7.2.J.2 of Appendix WSP1 to Annex 7.2/J of this Part.
3. Patrol reports shall be recorded in accordance with Table 7.2.J.3 of Appendix WSP1.

This is Annex 7.2/D to Schedule 7 Part 2 referred to in the foregoing Agreement between Scottish Ministers and BEAR Scotland Limited.

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/D – Snow Clearance

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/D – Snow Clearance

Table 7.2.D.1 – Snow Clearance

Condition Criteria	Category A Patrol Routes		Non Category A Patrol Routes	
	Dual Carriageways & Motorways		Dual Carriageways	Wide Single 2+1 (WS 2 + 1) & Single Carriageways
	Number of Existing Lanes		Number of Existing Lanes	
	2	3 or More	2	1 or 2 (WS 2 + 1)
	Minimum number of lanes in each direction free from ice and snow as far as is reasonably practicable		Minimum number of lanes in each direction free from ice and snow as far as is reasonably practicable (except where snow gates)	
Snow at any time	1	2	1	1
Following clearance of minimum lanes or the cessation of snow fall all lanes are to be clear of snow	6 hours	6 hours	12 hours	12 hours

This is Annex 7.2/E to Schedule 7 Part 2 referred to in the foregoing Agreement between Scottish Ministers and BEAR Scotland Limited.

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/E – Category A, B, C and D Footways, Footbridges and Cycling Facilities

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/E – Footways, Footbridges and Cycleways Categories A, B, C and D – Response Times and Clearance Requirements

Table 7.2.E.1 – Footways, Footbridges and Cycleways Categories A, B, C and D – Response Times and Clearance Requirements for Ice

Categories	Requirements
A and B	Apply de-icing treatment before 08.00 hours each morning to any ice which has formed.
C	Clear all ice by 17.00 hours on the same day the ice formed excluding Saturdays and Sundays when the area shall be cleared by 17.00 hours on the Monday immediately following.
A, B and C	Following clearance of ice or if ice has melted naturally during the day, spread anti-icing materials to prevent ice formation on the cleared surfaces in accordance with paragraph 3.1.17 of this Schedule.
D	These footways, footbridges and cycleways shall receive treatment when required by the Director.

Table 7.2.E.2 Footways, Footbridges and Cycleways Categories A, B, C and D – Response Times and Clearance Requirements for Snow or Ice Occurring Together

Categories	Requirements			
	General	Between 06.00 and 18.00 hours	Between 08.00 and 17.00 hours	Treatments out with daytime hours
A and B	Between the hours of 06.00 and 18.00, commence snow clearing as soon as practicable to prevent compaction by traffic. Ploughing should be continuous thereafter to prevent a build up of snow.	Clear all snow within 2 hours of snow ceasing to fall. On wide routes, 1.2 metre minimum width shall be cleared initially.		Clear snow when required by the Director.

Categories	Requirements			
C	Between the hours of 08.00 and 17.00, commence snow clearing as soon as practicable to prevent compaction by traffic. Ploughing should be continuous thereafter to prevent a build up of snow.		Clear all snow by 17.00 hours on the day the snow first fell excluding Saturdays and Sundays when the area shall be cleared on the Monday immediately following. On wide routes, 1.2 metre minimum width shall be cleared initially.	Clear snow when required by the Director.
A,B and C		Following clearance of snow, spread anti-icing materials to prevent ice formation on cleared surfaces in accordance with paragraph 3.1.17 of this Schedule. Note brine shall not be used as the anti-icing agent where compacted snow or ice lenses remain on the surface of the route.	Following clearance of snow, spread anti-icing materials to prevent ice formation on cleared surfaces in accordance with paragraph 3.1.17 of this Schedule. Note brine shall not be used as the anti-icing agent where compacted snow or ice lenses remain on the surface of the route.	
D	These footways, footbridges and cycleways shall receive treatment when required by the Director.			

Table 7.2.E.3– Category A, B and C Footways, Footbridges and Cycleways within the Unit

Location Number	Route	Location	Name of street/side of street to be treated	Details of Footway		Route Centreline Length (m)			
				Start	Finish	Category A	Category B	Category C	Category D
1	A82/A83	Tarbet		10826/70 ch 3795 (Speed Limit Signs)	10827/05 ch 415 (Filling Station)			870	
				16501/05 ch 0 (A82 Jct)	16501/05 ch 990 (Speed Limit Signs)			990	
2	A82/A85	Crianlarich		10836/80 ch 1340 (House Access)	10836/93 ch 335 (Railway Yard Access)			345	
				10836/93 ch 545 (Railway Bridge)	10837/04 ch 380 (End of Footway)			465	
				16302/82 ch 2590 (Speed Limit Signs)	16302/95 ch 470 (A82 Jct)			690	
3	A82	Tyndrum		10837/65 ch 2295 (Speed Limit Signs)	10837/65 ch 2835 (Filling Station)			540	
4	A82	Onich		10864/00 ch 2645 (Speed Limit Signs)	10864/70 ch 295 (Speed Limit Signs)			1540	
5	A82/A830	Fort William		10866/10 ch 8355 (Speed Limit Signs)	10869/00 ch 315 (Access to Trading Estate)			7831	
				17202/00 ch 0 (Loch Bridge Jct)	17202/00 ch 560 (Speed Limit Signs)			560	
6	A82/A86	Spean Bridge		10869/95 ch 355 (Speed Limit Signs)	10870/00 ch 305 (Speed Limit Signs)			690	
				12960/90 ch 10 (Junction)	12960/90 ch 493 (A82 Jct)			483	

Location Number	Route	Location	Name of street/side of street to be treated	Details of Footway		Route Centreline Length (m)			
				Start	Finish	Category A	Category B	Category C	Category D
7	A82	Fort Augustus		10877/75 ch 3740 (Speed Limit Signs)	10880/05 ch 545 (Speed Limit Signs)			1585	
8	A82/ A887	Invermoriston		10880/80 ch 1792 (Speed Limit Signs)	10880/80 ch 2273 (Junction with A887)			481	
				10885/05 ch 0 (Junction with A887)	10885/05 ch 172 (Speed Limit Signs)			172	
				12805/05 ch 0 (Junction with A82)	12805/05 ch 632 (Speed Limit Signs)			632	
9	A82	Drumnadrochit		10885/60 ch 3610 (Speed Limit Signs)	10890/05 ch 320 (Speed Limit Signs)			1890	
10	A82	Inverness		10890/90 ch 2460 (Speed Limit Signs)	10892/05 ch 1240 (THC HQ)			1700	
				10892/05 ch 1240 (THC HQ)	10892/05 ch 1515 (Kenneth St Junction)		420		
				10892/05 ch 1515 (Kenneth St Junction)	10898/05 (Rose St Roundabout)			1400	
				10898/05 (Rose St Roundabout)	10899/05 (Harbour Road Roundabout)	1100	1100		
				10899/05 (Harbour Road Roundabout)	10899/50 ch 150 (Speed Limit Signs)			700	
11	A828	Appin		17020/87 ch 2150 (Church)	17030/05 ch 390 (Bridge)			440	

Location Number	Route	Location	Name of street/side of street to be treated	Details of Footway		Route Centreline Length (m)			
				Start	Finish	Category A	Category B	Category C	Category D
12	A828	Benderloch & Ledaig		17010/33 ch 70 (Start of Footway)	17010/33 ch 1170 (Junction)			1100	
13	A83	Tarbert		16570/05 ch 20 (Start of Footway)	16570/06 ch 256 (End of Footway)			1232	
14	A83	Ardrishaig		16555/06 ch 626 (Ardrishaig Sign)	16565/05 ch 481 (Speed Limit Sign)			2938	
15	A83	Lochgilphead		16540/94 ch 0 (Speed Limit Signs)	16540/94 ch 240 (Manse Brae)			240	
				16540/94 ch 240 (Manse Brae)	16540/95 ch 325 (Lorne Street)		505		
				16540/95 ch 325 (Lorne Street)	16540/95 ch 455 (Speed Limit Sign)			130	
16	A83	Minard		16540/19 ch 0 (Speed Limit Signs)	16540/19 ch 970 (End of Footway)			970	
17	A83	Furnace		16540/05 ch 0 (Start of Footway)	16540/05 ch 515 (End of Footway)			515	
18	A83	Inveraray		16520/85 ch 2770 (Start of Footway)	16530/05 ch 140 (Start of Main Street)			150	
				16530/05 ch 140 (Start of Main Street)	16530/06 ch 90 (Church)		90		
				16530/06 ch 90 (Church)	16530/10 ch 410 (Speed Limit Signs)			1000	

Location Number	Route	Location	Name of street/side of street to be treated	Details of Footway		Route Centreline Length (m)			
				Start	Finish	Category A	Category B	Category C	Category D
19	A83	Arrochar & Succoth		16501/05 ch 2075 (Speed Limit Signs)	16512/05 ch 520 (Speed Limit Signs)			1895	
20	A830	Mallaig		17215/61 ch 1400 (Speed Limit Sign)	17215/61 ch 1630 (End of Trunk Road)			230	
21	A830	Arisaig		(Speed Limit Sign)	(Speed Limit Sign)			495	
22	A830	Corpach		17205/00 ch 350 (Speed Limit Signs)	17205/15 ch 30 (Speed Limit Signs)			2370	
23	A835	Contin		18004/50 ch 760 (Start of Footway)	18006/06 ch 472 (Speed Limit Signs)			1232	
24	A835	Garve		18006/76 ch 3217 (Start of Footway)	18008/06 ch 250 (End of Footway)			760	
25	A835/ A893	Ullapool		18012/75 ch 3000 (Braes Junction)	18012/75 ch 4020 (A835/A893 Jct)			1020	
				18014/05 ch 0 (A835/A893 Jct)	18014/05 ch 370 (Ferry Terminal)		370		
26	A84	Doune		16212/68 ch 0 (Speed Limit Signs)	16213/04 ch 212 (Speed Limit Signs)			1122	
27	A84	Burn of Cambus		16213/06 ch 940 (Speed Limit Signs)	16213/06 ch 1595 (Speed Limit Signs)			655	
28	A84	Callander		16215/05 ch 0 (Speed Limit Signs)	16215/38 ch 115 (Menteith Crescent)			975	

Location Number	Route	Location	Name of street/side of street to be treated	Details of Footway		Route Centreline Length (m)			
				Start	Finish	Category A	Category B	Category C	Category D
				16215/38 ch 115 (Menteith Crescent)	16220/04 ch 120 (Ancaster Road)	825	825		
				16220/05 ch 0 (Ancaster Road)	16220/05 ch 830 (Speed Limit Signs)			830	
29	A84	Kilmahog		16220/48 ch 584 (Start of Footway)	16220/48 ch 895 (End of Footway)			311	
30	A84	Strathyre		16225/51 ch 2705 (Start of Footway)	16225/58 ch 610 (End of Footway)			665	
31	A84/ A85	Lochearnhead		16225/94 ch 0 (Speed Limit Signs)	16225/94 ch 570 (A85 Jct)			570	
				13930/81 ch 585 (Start of Footway)	16301/03 ch 190 (End of Footway)			743	
32	A85	Oban		11940/05 ch 815 (Speed Limit Signs)	11940/34 ch 490 (Dunollie Road)			605	
				11940/71 ch 0 (Dunollie Road)	11940/56 ch 0 (Corran Esplanade)		1090		
				11940/89 ch 0	11940/94 ch 130 (End of Trunk Road)			290	
33	A85/ A828	Connel		11920/80 ch 5790 (Speed Limit Signs)	11930/05 ch 580 (Speed Limit Signs)			1810	
				17010/05 ch 0 (A85 Jct)	17010/06 ch 220 (Speed Limit Signs)			890	

Location Number	Route	Location	Name of street/side of street to be treated	Details of Footway		Route Centreline Length (m)			
				Start	Finish	Category A	Category B	Category C	Category D
34	A85	Taynuilt		11920/52 ch 2890 (Junction)	11920/65 ch 830 (End of Footway)			1740	
35	A85	Lochawe		11920/05 ch 1955 (Speed Limit Signs)	11920/18 ch 550 (Filling Station)			2045	
36	A85	Dalmally		11910/80 ch 2450 (Start of Footway)	11910/80 ch 3430 (Dalmally Jct)			980	
37	A85	St. Fillans		13925/58 ch 0 (Junction)	13925/58 ch 1390 (Junction)			1390	
38	A85	Comrie		13920/85 ch 0 (Speed Limit Signs)	13925/07 ch 365 (Bridge Jct)			1263	
39	A85	Crieff		13915/60 ch 0 (Speed Limit Signs)	13915/60 ch 905 (Dollerie Street)			905	
				13915/67 ch 0 (Dollerie Street)	13915/80 ch 130 (Burrell Street)	738	738		
				13915/80 ch 130 (Burrell Street)	13920/10 ch 872 (Speed Limit Signs)			956	
40	A85	Gilmerton		13910/99 ch 45 (Junction)	13915/05 ch 178 (Speed Limit Signs)			382	
41	A85	Methven		13910/27 ch 150 .. (Start of Footway)	13910/37 ch 70 (Speed Limit Signs)			1072	
42	A85	Perth & Huntingtower		13905/10 ch 0 (Roundabout)	13910/07 ch 20 (Speed Limit Signs)			809	

Location Number	Route	Location	Name of street/side of street to be treated	Details of Footway		Route Centreline Length (m)			
				Start	Finish	Category A	Category B	Category C	Category D
				13910/07 ch 620 (Speed Limit Signs)	13910/10 ch 90 (End of Footway)			1153	
43	A86	Kingussie		12915/40 ch 0 (Speed Limit Signs)	12915/40 ch 265 (Manse Road)			265	
				12915/40 ch 265 (Manse Road)	12915/40 ch 795 (Station Road)		530		
				12920/05 ch 0 (Station Road)	12920/05 ch 465 (Speed Limit Signs)			465	
44	A86	Newtonmore		12920/10 ch 2730 (Speed Limit Signs)	12920/70 ch 965 (Primary School)			1191	
				12920/70 ch 965 (Primary School)	12920/70 ch 1353 (B9150 Jct)		388		
				12925/05 ch 0 (B9150 Jct)	12925/05 ch 25 (End of Footway)			25	
				12925/05 ch 200 (Hotel Entrance)	12925/05 ch 450 (End of Footway)			250	
45	A87	Uig		17493/60 ch 65 (Start of Footway)	17495/05 ch 1322 (End of Trunk Road)			2647	
46	A87	Kensaleyre		17485/05 ch 990 (Speed Limit Signs)	17485/05 ch 1990 (End of Footway)			1000	
47	A87	Portree		17465/05 ch 1815 (Speed Limit Signs)	17475/05 ch 340 (Junction)			1901	

Location Number	Route	Location	Name of street/side of street to be treated	Details of Footway		Route Centreline Length (m)			
				Start	Finish	Category A	Category B	Category C	Category D
48	A87	Broadford		17430/05 ch 0 (A851 Jct)	17440/15 ch 40 (Junction)			2826	
49	A87	Kyle of Lochalsh & Kyleakin		17410/96 ch 0 (Speed Limit Signs)	17412/30 ch 90 (Toll Station)			1269	
				17415/05 ch 0 (Bridge Barrier)	17415/20 ch 210 (Restaurant Entrance)			319	
50	A87	Balmacara		17410/00 ch 2700 (Speed Limit Signs)	17410/00 ch 3200 (Speed Limit Signs)			500	
51	A87	Inverinate		17406/00 ch 3850 (Speed Limit Signs)	17406/00 ch 4630 (Glebe Road Jct)			780	
				17406/00 ch 6500 (Access to House)	17406/00 ch 7375 (Local Road Jct)			875	
52	A87	Invergarry		17400/00 ch 60 (Speed Limit Signs)	17400/15 ch 65 (Speed Limit Signs)			1235	
53	A889	Dalwhinnie		12705/20 ch 145 (Opposite Hotel)	12705/20 ch 922 (Speed Limit Signs)			777	
54	A9	Thurso & Scrabster		10515/50 ch 3905 (Speed Limit Signs)	10530/05 ch 225 (Janet Street)			460	
				10530/05 ch 225 (Janet Street)	10530/11 ch 50 (Olig Street, Thurso)	335	335		
				10530/11 ch 50 (Olig Street, Thurso)	10535/05 ch 2140 (Ferry Terminal)			3170	

Location Number	Route	Location	Name of street/side of street to be treated	Details of Footway		Route Centreline Length (m)			
				Start	Finish	Category A	Category B	Category C	Category D
55	A9	Helmsdale		10485/85 ch 1360 (Speed Limit Signs)	10489/10 ch 50 (End of Footway)			390	
56	A9	Portgower		10485/55 ch 3180 (Start of Footway)	10485/75 ch 260 (End of Footway)			490	
57	A9	Brora		10482/40 ch 3540 (Bus Stop)	10483/05 ch 430 (Gower Street)			500	
				10483/05 ch 430 (Gower Street)	10483/50 ch 225 (Filling Station)		545		
				10483/50 ch 225 (Filling Station)	10485/05 ch 45 (45m north of Clynelish Rd)			1100	
58	A9	Golspie		10480/06 ch 4720 (Speed Limit Signs)	10480/65 ch 555 (War Memorial)			815	
				10480/65 ch 555 (War Memorial)	10480/65 ch 1510 (Duke Street)		955		
				10480/65 ch 1510 (Duke Street)	10482/05 ch 115 (Speed Limit Signs)			525	
59	A99	Wick		10492/95 ch 5950 (Speed Limit Signs)	10492/96 ch 460 (West Banks Ave)			580	
				10492/96 ch 460 (West Banks Avenue)	10492/96 ch 730 (End of Trunk Road)		270		
60	A99	Lybster		10492/20 ch 1720 (Start of Footway)	10492/25 ch 155 (End of Footway)			335	

This is Annex 7.2/F to Schedule 7 Part 2 referred to in the foregoing Agreement between Scottish Ministers and BEAR Scotland Limited.

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/F – Location of Known Areas Requiring Special Attention

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/F – Location of Known Areas Requiring Special Attention

Table 7.2.F.1 – Frost Susceptible Areas

Road Number	Location of Frost Susceptible Area
A82	Glen Gloy Bends
A82	Three Mile Water
A82	Spean Bridge
A82	A82 Glencoe
A82	A82 Bridge of Orchy
A83	Auchindrain
A830	Glenfinnan
A830	Mhuide Hill
A830	West of Loch Eilt
A835	Inchbae
A835	South of Aultguish
A84	Dandues Brae, Doune
A85	South of Strone
A85	Glen Lochy
A85	Dunira
A85	A85 Glen Dochart – Lix Toll
A85	St. Fillans - Lochearnhead
A85	Glen Ogle

Road Number	Location of Frost Susceptible Area
A86	Tulloch
A86	A86 Strathmashie
A86	Near Glen Spean
A86	A86 Near Cromra
A87	Glen Varragill
A87	Glenshiel
A87	Kinlochoum
A887	Near Dundreggan
A9	Latheron to Mybster
A9	Berriedale
A9	Daviot
A9	Loch Faskally
A9	Killiecrankie
A9	Kingussie
A9	Near Dalwhinnie
A9	Slochd
A9	Findhorn

Table 7.2.F.2 – Water Run Off Locations

Road Number	Water Run Off Location
A82	West of Cobb Memorial
A82	Inverarnan to Tarbet
A83	Artilligan to Stronachullin
A83	Stonefield

Road Number	Water Run Off Location
A83	Mundells, Tarbet
A83	Cairndow Hill
A83	Strone Point to Dunderarve
A830	West of Loch Eilt
A835	West of Tarvie
A84	Leny Falls
A85	A85 Glen Dochart – Lix Toll
A85	St. Fillans - Lochearnhead
A85	Glen Ogle
A85	Loch Awe to Brander Lodge
A85	Abercairney
A85	Ochertyre
A85	Cultoquay
A86	Near Glen Spean
A86	A86 Near Cromra
A9	Achavanich to Tacher
A9	Dunbeath Mains
A9	Knockinnon
A9	Newport
A9	Keepers Cottage Ousdale
A9	Layby 190
A9	Balvraid
A9	Daviot Northbound
A9	Moy

Road Number	Water Run Off Location
A99	Borrowston Quarry

Table 7.2.F.3 – Gradient Locations

Road Number	Location
A82	Tyndrum to Glencoe
A83	Rest and Be Thankful
A85	Glen Ogle
A87	Invergarry – Bun Loyne – Sheil Bridge
A887	Invermoriston - Bun Loyne
A889	Catlodge to Dalwhinnie
A9	Ord of Caithness
A9	Berriedale Braes
A9	Drum Mossie Brae (Southbound)
A9	Calvine to Dalnaspidal

This is Annex 7.2/G to Schedule 7 Part 2 referred to in the foregoing Agreement between Scottish Ministers and BEAR Scotland Limited.

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/G – Location Details

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/G – Location Details

Locations of Snow Fences, Snow Gates: as shown in Table 7.2.G.1.

Locations of Hidden Message Signs: as shown in Table 7.2.G.2.

Locations of Road Sensors Forecast Sites: as shown in Table 7.2.G.3.

Locations of Snow Poles: as shown in Table 7.2.G.4.

Locations of vertical concrete barriers: as shown in Table 7.2.G.5.

Table 7.2.G.1 – Locations of Snow Fences, Snow Gates and Salt Bins

Road Number	Snow Fence (Meters)	Snow Gates (Number)	Salt Bins (Number)
A9	1630	8	15
A99	0	0	0
A82	0	3	10
A83	0	0	7
A830	0	0	0
A835	850m	2	4
A84	0	0	2
A85	0	0	4
A86	0	0	0
A87	0	0	3
A887	0	0	4
A889	0	2	0
A893	0	0	0
A828	0	0	0

Table 7.2.G.2 – Locations of Hidden Message Signs

Road Number.	Location	Detailed Description
A82	Tyndrum	Snow Gate
A82	Ballachullish Roundabout	Fibre Optic (Fixed Message) Sign
A82	Bridge of Orchy	Snow Gate
A82	Glencoe Garage	Sign Type 554
A82	North Ballachullish	Sign Type 554
A82	Clifton	Snow Gate
A82	Fort William	Fibre Optic (Fixed Message) Sign
A82	Glencoe Police Station	Snow Gate
A82	Invergarry	Fibre Optic (Fixed Message) Sign
A830	Muidhe	Sign Type 554

Road Number.	Location	Detailed Description
A830	Craigag Bridge	Sign Type 554
A830	Glenfinnan	Sign Type 554
A830	Banavie	Sign Type 554
A835	Altguish Hotel	Snow Gate
A835	Braemore Junction	Snow Gate
A835	Contin	Fibre Optic (Fixed Message) Sign
A835	Garve	Fibre Optic (Fixed Message) Sign
A835	Maryburgh	Fibre Optic (Fixed Message) Sign
A835	Ullapool	Fibre Optic (Fixed Message) Sign
A87	17404/00 ch 2797	Sign Type 554
A87	17404/00 ch 3133	ICESEN
A87	Cluanie	Fibre Optic (Fixed Message) Sign
A87	Invergarry	Fibre Optic (Fixed Message) Sign
A9	Berriedale	Snow Gate
A9	Dunbeath	Snow Gate
A9	Dalwhinnie Junction	Snow Gate
A9	Blair Atholl south Junction	Snow Gate
A9	Georgemas Junction	Fibre Optic (Fixed Message) Sign
A9	Helmsdale	Fibre Optic (Fixed Message) Sign
A9	Navidale	Snow Gate
A9	Ralia Junction	Snow Gate
A9	Blackmount	Sign Type 554
A9	Trinafour	Snow Gate
A9	Essangael	Snow Gate

Table 7.2.G.3 – Locations of Road Sensors and Forecast Sites

Road Number	Location
A82	Allt na Feadh
A82	Inchnacardoch
A82	Friars Bridge
A82	Invergarry
A82	Spean Bridge
A82	Tarbet
A82	Torvean
A82	West Laroach
A82	Tyndrum
A83	Furnace
A83	Glen Croe
A83	Kennacraig
A830	Blar mor
A830	Morar
A830	Glenfinnan
A835	Braemore

Road Number	Location
A835	Brahan
A835	Aultguish
A84	Drumvaich
A84	Glenogle
A85	Dalmally
A85	McAras Brae
A85	Tofts
A86	Roy Bridge
A86	Tullochroam
A87	Cluanie
A87	Glen Varragill
A87	Ard Dorch
A87	Skye Bridge
A887	Achlain
A889	Catlodge
A9	Achavanich
A9	Avielochan
A9	Balvraid
A9	Berriedale
A9	Bogbuie
A9	Calvine
A9	Daviot
A9	Delny
A9	Dornoch Bridge
A9	Drumochter
A9	Dunkeld
A9	Kessock Bridge
A9	Logie Easter
A9	Lybster
A9	Ord Ousdale
A9	Slochd
A9	Sordale
A828	Barcaldine

Table 7.2.G.4 – Locations of Snow Poles

Route A83					
Link	Section	Start Chainage	End Chainage	Spacing (metre)	Number
16512	19	4400	6930	50	50
16512	19	4400	6930	50	50
16512	59	0	2370	50	47
16512	59	0	2370	50	47
16512	73	0	3600	50	72
16512	73	0	3600	50	72
				Total	338

Route A85					
Link	Section	Start Chainage	End Chainage	Spacing (metre)	Number
11910	05	0	680	50	14
11910	05	0	680	50	14
11910	08	0	2608	50	52
11910	08	0	2608	50	52
11910	20	0	3206	50	64
11910	20	0	3206	50	64
11910	37	0	4964	50	99
11910	37	0	4964	50	99
11910	59	0	3957	50	79
11910	59	0	3957	50	79
				Total	616

Route A835					
Link	Section	Start Chainage	End Chainage	Spacing (metre)	Number
18010	05	30	2040	50	40
18010	10	80	200	50	2
18010	50	2335	4240	50	38
18010	50	3779	4240	50	9
18010	60	0	6470	50	129
18010	60	0	6470	50	129
18010	70	0	7880	50	157
18010	70	0	7880	50	157
				Total	661

Route A86					
Link	Section	Start Chainage	End Chainage	Spacing (metre)	Number
12940	65	90	3236	50	64
12940	65	90	3236	50	64
12940	65	200	400	50	5
12940	65	100	400	50	4
				Total	137

Route A899					
Link	Section	Start Chainage	End Chainage	Spacing (metre)	Number
12705	05	0	180	50	3
12705	05	0	180	50	3
12705	05	865	1170	50	6
12705	05	865	1170	50	6
				Total	18

Route A82					
Link	Section	Start Chainage	End Chainage	Spacing (metre)	Number
10838	05	0	2632	50	52
10838	05	0	2632	50	52
10850	05	260	3156	50	57
10850	05	260	3156	50	57
10850	11	15	3214	50	63
10850	11	15	3214	50	63
10850	45	45	3165	50	62
10850	45	45	3165	50	62
10850	56	16	1097	50	21
10850	56	16	1097	50	21
10861	00	41	8981	50	178
10861	00	41	8981	50	178
10861	25	0	2515	50	50
10861	25	0	2515	50	50
10861	35	0	5797	50	115
10861	35	0	5797	50	115
10861	45	0	1200	50	24
10861	45	0	1200	50	24
				Total	1244

Route A9(N)					
Link	Section	Start Chainage	End Chainage	Spacing (metre)	Number
10489	20	0	2120	50	42
10489	25	350	740	50	7
10489	25	1135	1404	50	5
10489	30	0	1130	50	22
10489	60	165	330	50	3
				Total	79

Route A9(S)					
Link	Section	Start Chainage	End Chainage	Spacing (metre)	Number
10440	44	765	1315	50	11
10440	44	3300	3800	50	10
10440	44	4170	4460	50	5
10440	44	6860	8255	50	27
10440	44	6860	8255	50	27
10440	66	0	1317	50	26
10440	67	0	1312	50	26
10440	70	0	4540	50	90
10440	70	5350	8481	50	62
10440	81	0	8446	50	168
10440	92	0	3250	50	65
10440	92	0	3250	50	65
10441	0	0	7269	50	145
10441	0	0	7269	50	145
10442	05	0	4356	50	87

Route A9(S)					
Link	Section	Start Chainage	End Chainage	Spacing (metre)	Number
10442	05	0	4356	50	87
10442	25	0	5233	50	104
10442	25	0	5233	50	104
10442	50	0	1344	50	26
10442	51	0	1338	50	26
10446	75	1600	1920	50	6
10446	75	1800	2630	50	16
10447	05	0	851	50	17
10447	05	0	851	50	17
10447	10	260	900	50	12
10447	10	260	900	50	12
				Total	1386

Table 7.2.G.5 – Locations of Vertical Concrete Barriers

Route NONE					
Link	Section	Start Location	End Location	No.	Link

This is Annex 7.2/H to Schedule 7 Part 2 referred to in the foregoing Agreement between Scottish Ministers and BEAR Scotland Limited.

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/H – Records

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/H – Records

- 1 Records shall include the following:
 - (i) decisions taken, when and by whom,
 - (ii) planned and actual treatment records,
 - (iii) planned and actual response times achieved,
 - (iv) planned and actual commencement times,
 - (v) planned and actual route times,
 - (vi) planned and actual spread rates,
 - (vii) observations and actions taken by the Winter Service Patrols,
 - (viii) output from Winter Service Plant on-board data capture devices,
 - (ix) Winter Service Plant down time and software faults,
 - (x) Winter Service Plant deployment records (including vehicle location records) and driver and operator logs,
 - (xi) logs (both manual and electronic) for telephone, electronic mail and two way communication calls,
 - (xii) loading point de-icing stocks and replenishment orders,
 - (xiii) ice prediction system Records,
 - (xiv) weather forecasts and actual weather experienced,
 - (xv) complaints by members of the public and Trunk Road users,
 - (xvi) accidents during winter conditions,
 - (xvii) road closures due to winter conditions,
 - (xviii) weights and volumes as appropriate for the amount of de-icing material(s) spread for each route,
 - (xix) pre- and mid-season road sensor calibration systems,
 - (xxi) Winter Service Plant calibration certificates, and
 - (xxii) actual salt stocks held including strategic salt stocks.

This is Annex 7.2/I to Schedule 7 Part 2 referred to in the foregoing Agreement between Scottish Ministers and BEAR Scotland Limited.

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/I – Potassium Acetate Treatment

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/I – Potassium Acetate Treatment

Potassium acetate treatment shall be applied at the location specified in Table 7.2.I.1 including those parts of the Trunk Road 200 metres beyond the limits of each bridge.

Table 7.2.I.1

Road Number	Location
A9	Kessock Bridge
A82	Friars Bridge and Approaches
A9	Cromarty Bridge
A9	Dornoch Bridge
A87	Carrich Bridge
A87	Skye Bridge

This is Annex 7.2/J to Schedule 7 Part 2 referred to in the foregoing Agreement between Scottish Ministers and BEAR Scotland Limited.

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/J – Appendices for Winter Service Plan

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/J – Appendices for Winter Service Plan

APPENDIX WSP1

Table 7.2.J.1 – Winter Service Plant for all Winter Service Patrols

COMMERCIALLY SENSITIVE INFORMATION REDACTED

Table 7.2.J.2 – Winter Service Patrol Routes

COMMERCIALLY SENSITIVE INFORMATION REDACTED

Table 7.2.J.3 – Winter Service Patrol Report Record

Patrol Route..... Date..... Information checked by.....

Winter Service Patrol start and end time	Weather conditions for Winter Service Patrol route		Assessed road condition (by driver) (X)				Assessed residual salt level (by driver) (X)			Action implemented (use symbols provided below)*						Route salted prior to patrol (X)		
	Air (°C)	Road Surface temperature (°C)	Snow	Icy	Wet	Dry	High	Medium	Low	Action code	Treatment Type	Spread rate (g/m ²)	Approximate location of salting or other action	Treatment Start Time	Treatment End Time	Yes	No	Time of salting

*Action symbols:

- 1

Spot treatment as instructed by the Winter Service Duty Officer.
- 2

Spot treatment as determined by driver.
- 3

Route treatment as advised by the Winter Service Duty Officer.
- 4

Route treatment as determined by driver.
- 5

Attend to runoff or seepage on surface.
- 6

Remove obstruction (eg dead dog, fallen tree, and other obstructions.) from surface.
- 7

Pre-wetted Salt
- 8

Dry Salt
- 9

Potassium Acetate

APPENDIX WSP2

Table 7.2.J.4 - Precautionary Treatment Routes determined by the Operating Company

COMMERCIALLY SENSITIVE INFORMATION REDACTED

Table 7.2.J.5 - Ploughing Routes determined by the Operating Company

COMMERCIALLY SENSITIVE INFORMATION REDACTED

APPENDIX WSP3

Table 7.2.J.6 – Operational Salt Stock Levels

Minimum Salt Stock Level at Start of Season (tonnes)
32,000

COMMERCIALLY SENSITIVE INFORMATION REDACTED

Table 7.2.J.7 –Brine Production and Storage

COMMERCIALLY SENSITIVE INFORMATION REDACTED

APPENDIX WSP4

The Operating Company's Winter Service Plant

Table 7.2.J.8 - Front line Winter Service Plant permanently available and located in the Unit for Winter Service for carriageways

COMMERCIALLY SENSITIVE INFORMATION REDACTED

Table 7.2.J.9 - Front line Winter Service Plant permanently available and located in the Unit for the Winter Service for footways footbridges and cycling facilities

COMMERCIALLY SENSITIVE INFORMATION REDACTED

Table 7.2.J.10 - Reserve Winter Service Plant permanently available and located in the Unit for Winter Service for carriageways footways footbridges and cycling facilities

COMMERCIALLY SENSITIVE INFORMATION REDACTED

Table 7.2.J.11 - Additional Winter Service Plant

COMMERCIALLY SENSITIVE INFORMATION REDACTED

Table 7.2.J.12 - Loading Winter Service Plant permanently available and located in the Unit at each loading point

COMMERCIALLY SENSITIVE INFORMATION REDACTED

APPENDIX WSP5

The Operating Company's Compounds, Depots and Facilities

Table 7.2.J.13 – The Operating Company's Compounds, Depots and Facilities

COMMERCIALLY SENSITIVE INFORMATION REDACTED

This is Annex 7.2/K to Schedule 7 Part 2 referred to in the foregoing Agreement between Scottish Ministers and BEAR Scotland Limited.

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/K – Requirements for De-Icing Material Spread Rates

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/K – Requirements for De-Icing Material Spread Rates

Table 7.2.K.1 – Decision Making Process for Winter Service

Table 7.2.K.1 sets out the decision making process for winter service:

Decision Matrix			
	Predicted Road Conditions		
Road Surface Temperature	Wet	Wet Patches	Dry
May fall below 1°C	Salt before frost	Salt before frost (See note A)	No action likely, monitor weather (See note A)
Expected to fall below 1°C		Salt before frost (see note B)	
		Salt after rain stops	
		Salt before frost and after rain stops (see note C)	
		Salt before frost	Monitor weather conditions
Expected snow		Salt before snow	
Freezing Rain	Salt before rainfall (see note C)		
	Salt during rainfall (see note C)		
	Salt after rainfall (see note C)		
The decision to undertake precautionary treatments should, if appropriate, be adjusted to take account of residual salt or surface moisture.			

A. Particular attention should be given to any possibility of water running across carriageways and such locations should be monitored and treated as required.

B. When a weather warning contains reference to expected hoarfrost considerable deposits of frost are likely to occur and close monitoring will be required. Particular attention should be given to the timing of precautionary treatments due to the possibility that salt deposited on a dry road may be dispersed before it can become effective.

C. Under these circumstances rain will freeze on contact with running surfaces and full pre-treatment should be provided even on dry roads. This is a most serious condition and should be monitored closely and continuously throughout the danger period.

Table 7.2.K.2 – Forecast Weather and Road Conditions Status Codes and Treatment Rates

Table 7.2.K.2 sets out the forecast weather and road condition status codes and treatment rates. Rate of spread for precautionary treatments may be adjusted to take account of residual salt or surface moisture unless stated otherwise.

A road is considered to be only damp when water is present that clearly darkens the road surface, but there is no spray or water flowing across the surface. A wet road is one where minimal spray is evident and there is no water flowing across the surface and no drops of water are formed by trafficking. A very wet road is one where trafficking causes drops of water to form in the air; higher spread rates are required for very wet roads or successive treatments are needed.

National research has shown that salt spreading equipment may be delivering more or less than the targeted salt spread rates within the traffic lanes. The research has also shown that residual salt levels reduce remarkably during the initial 12 hours after distribution regardless of whether dry, treated or pre-wetted salting techniques are employed. The loss can be as much as one and a half of the initial material spread during this period on a heavily trafficked road in dry conditions.

Protection is only achieved when salt is fully dissolved before forecast conditions occur and treatments should be timed to take account of this.

Spread rates for pre-wetted salt are the combined weight of dry rock salt and brine combined at 70:30 proportion by weight respectively with a maximum brine concentration of 23 percent salt.

Treatments should be carried out, wherever possible after traffic has dispersed standing water. The rates in the table below are for precautionary salt treatment prior to snowfall which is essential to form a de-bonding layer and snow clearance.

Operational experience has indicated that thin surfacing courses do not benefit from an increase in dosage above that required for hot rolled asphalt but that the effect of residual salt on the carriageway is reduced particularly in areas of low traffic, and as such treatment can be applied more frequently. Treatment of thin surface courses should be treated with caution: residual salt should not be relied upon to provide protection: and if there is any hint of moisture being present a pessimistic view of the forecast should be taken.

Table 7.2.K.2 – Treatment Matrix

Treatment Matrix Spread rates for precautionary treatments		
Forecast weather condition	Frost Susceptible/surface water run-off area (grammes/square metre)	Road Surface Wet (grammes/square metre)
A. RST higher than plus 1°C	0	0
B. RST lower than or equal to plus 1°C but higher than minus 2°C	10 to 20	10 to 20
C. RST lower than or equal to minus 2°C but higher than minus 5°C	10 to 20	10 to 20
D. RST lower than or equal to minus 5°C	20	20
E. RST lower than or equal to plus 1°C but higher than minus 2°C following rain	20	30
F. RST lower than or equal to minus 2°C but higher than minus 5°C following rain	30	40
G. RST lower than or equal to minus 5°C following rain	40	40
H. Hoar Frost	20	20
I. Freezing Fog	10	20
J. Freezing Rain	40 (See decision matrix)	40 (See decision matrix)
K. Snow Accumulations up to 30mm	30	40
L. Snow Accumulations over 30mm	40	40
M. Hard Packed Snow/Ice	See clearance matrix	See clearance matrix

Table 7.2.K.3 –Precautionary Treatment Potassium Acetate Spreading Rates

CONDITIONS FORECAST	SPREAD RATE (litres/square metres)
Road surface temperature lower than or equal to plus 1°C but higher than minus 2°C	0.0156
Road surface temperature lower than or equal to minus 2°C but higher than minus 5°C	0.0312
Frost and road surface temperature lower than -5°C	a minimum of 0.0312 which should be increased with manufacturer's recommendations
Snow	
Freezing conditions after rain	

Table 7.2.K.4 – Snow or Ice Clearance Salt Spreading Rates

Clearance Matrix			
Minimum Salt Spread rates for Snow or Ice Clearance			
Road Surface Condition	Treatment		
	Spreading (grammes/square metre)	Ploughing	Blowing
	Salt		
Ice Formed	20 to 40	No	No
Snow covering of less than 30mm	20	Yes	No
Snow covering exceeds 30mm	20 to 40	Yes	No
Snow accumulations due to prolonged snowfall	20 to 40	Yes (continuous)	Where applicable
Hard packed snow/ice less than 20mm thick	20 to 40 (successive treatments)	No	No
Hard packed snow/ice	salt/abrasive (successive)	No	No

This is Annex 7.2/L to Schedule 7 Part 2 referred to in the foregoing Agreement between Scottish Ministers and BEAR Scotland Limited.

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/L – Salt Stock Monitoring Report

SCOTTISH MINISTERS' REQUIREMENTS

SCHEDULE 7 PART 2

WINTER SERVICE

ANNEX 7.2/L – Salt Stock Monitoring Report

Operating Company	Reporting Month
Salt used during reporting period	
Actual salt stocks held at the end of the reporting period	
Salt orders placed and deliveries received during reporting period	
Salt orders expected during next reporting period (include imports, dates deliveries expected & tonnage expected)	
Forecast usage during next reporting period	
Any other items to report (such as reduced treatment networks, any notable arrangements with local authorities, etc.)	